

## INTERNATIONAL TRUCK AND ENGINE CORPORATION

EXECUTIVE ORDER U-R-012-0055 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2002	2NVXL0530AND	8.7	Diesel	8000				
SPECIAL	FEATURES & EMISSION	····	TYPICAL EQUIPMENT APPLICATION					
	Direct Diesel Injection, Tu and Engine Control !	urbocharger Module	Generato	r				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION			i	EXHAUST (g/kw-i		OPACITY (%)				
	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK	
130 <u>&lt;</u> KW<225	Tier 1	STD	1.3	9.2	N/A	11.4	0.54	N/A	N/A	N/A	
		CERT	0.1	7.6		1.1	0.08				

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

\_ day of December 2001.

R. B. Suramerfield, Chief

Mobile Source Operations Division

## ATTAC YENT 1 OF 1

Engine Model Sv nary Form

Manufacturer: International E. O. # U-R-12-55

Engine category: Nonroad CI

EPA Engine Family: 2NVXL0530AND

Mfr Family Name: DT 530E

Process Code: New Submission

		1.6.	h. 11	4.2						F.	14.7	· ·.			on the state of th	: [ ]		riiki j		
rol 1930		-	_	_		_										() ()			1.51 154	
9.Emission Control Device Per SAE J1930		ပ်	် ပ	ECM, TC, DI	о П	ار ت		-							14 G	W.	Y J			
lissior Per 9		M,T	Σ̈́	ĭ.	Σ	ECM, TC,											d F			
9.Em		낊	П	В	П	Ы					7 mg	•		1 T						
_												;					11 4		ers ar E	
8.Fuel Rate: (lbs/hr)@peak torque	ge	_	_			_			1.					11 5.1		•				
8.Fuel Rate: nr)@peak to	Average	Ž	Ϋ́	Ž	₹	Ϋ́		:						* *			<i>i</i> -		100	
8.F ss/hr)	4													e V Aus					1	
_									٠.											
7.Fuel Rate: mm/stroke@peak torque	ge																			
7.Fuel Rate: n/stroke@pe torque	Average	ž	Ž	ž	Ϋ́	ž											1. 1.		18.7° 1887	
7.Fi nm/st t	۷																			
C				:								:				14 1 - 1 1 - 1	Ž.			
SPM (s	p							;				:				, ,				
e @ F Gros	Advertised	¥	₹	¥	Ϋ́	Ϋ́					ر زرگ پرست ۱۳۵۵ تا			# 10 h		3		1800 A		
6.Torque @ RPM (SEA Gross)	Adv			-		-		ı				:					e. G			
O												,								
. H ≨												-							1. A.	
5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)	Average	78.0	81.4	73.9	72.7	64.6				:									4.	200
.Fuel hr) @ r dies	Ave	32	ထ်	22	7	9														
(foi												:				 				
표																1 22	<b>N</b>			40.1
tate: peak only	эде	7	0	9	. · · ·	ဖ					i de Ser					ď.			"	7
4.Fuel Rate: stroke @ peal or diesel only	Average	155.2	135.0	122.6	144.7	128.6					44					:	1. 19 14		•	
4.Fuel Rate: mm/stroke @ peak (for diesel only)														18 1875   14 1875   14		٠.,				
Ε																				
RPM (ses)	peg	500	800	800	200 @ 1500	500	ither	ō	2	) or	ट	5 or	75						4	
3.BHP@RPM (SAE Gross)	Advertised	215 @ 1500	(0)	(a) 1	0	<u>@</u>	pe e	GCA230 or	GCB200	GCA230 or	GCB215	GCA205 or	GCB175			i.	` 			
3.B (SA	Ą	215	230	205 @ 1800	200	175	can be either	29	Ö	ည	Ö	GC	Ö							1
														William Name						
2.Engine Model		ю		വ	0	ഹ		0	ē.	:	٠. ٠	Ŋ	.1							
ne N		GCB215	GCA230	GCA205	GCB200	GCB175		GCD230		)230	3 + 2 + 2	GCD205					:			
Engi		ဗ္ဗ	ပ္ပ	္မတ္	ဗ္ဗ	ဗ္ဗ		g		GCD230A	i v	၁၅								,
2.										:					:			* :		
apo							<u>.</u>			مہر	• . • · •			5 k 2 kg						
ة ر		GCB215	GCA230	GCA205	GCB200	GCB175	ating	GCD230		230/		GCD205								i i
1.Engine Code		GCE	200	CC/	GCE	GCE	Dual ratings	GCL		GCD230A		GCE			Į.	•				
7		: !	`. 				۵				: 									