



ISUZU MOTORS LIMITED

EXECUTIVE ORDER U-R-006-0108 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2002	2SZXL09.8EXA	9.8	Diesel	8000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT	APPLICATION		
	Direct Diesel Injec Turbocharger, Charge	tion, Air Cooler	Crane, Loader, Generator, Excavator			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
CLASS	CATEGORY		HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
225 ≤ KW < 450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	20	15	50
		CERT			6.3	1.4	0.19	18	4	49

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _______ day of December 2001.

R. B. Summerfield, Chief

Papal Surrout

Mobile Source Operations Division

Engine Model Summary Form

Engine category: Nonroad CI Isuzu Motors Limited

Manufacturer:

EPA Engine Family. 2SZXL09.8EXA

Mfr Family Name:

Process Code:

New Submission

7TTACHMENT

<u>а</u> П U-R-006-0108

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930
6SD1XABEA-01	AA-6SD1X	333.1@2200	176.0@2200	129.2@2200	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,DD
6SD1XABEA-02	AA-6SD1X	317.0@1750	191.0@1750	111.5@1750	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,D)I
6SD1XABEA-03 ★	AA-6SD1X	237.9@2200	126.0@2200	92.5@2200	738.0@1600	135.0@1600	72.1@1600	EM,TC,CAC,Db;
6SD1XABEA-04★	AA-6SD1X	169 L 227.3@1750	138.0@1750	80.6@1750	738.0@1600	135.0@1600	72.1@1600	EM,TC,CAC,DD!
6SD1XABEA-05	AA-6SD1X 25	2 _{40 2} 335.4@1950	187.0@1950	121.6@1950	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,Db1
6SD1XABEB-01	AA-6SD1X	333.1@2200	176.0@2200	129.2@2200	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DDI
6SD1XABEB-02	AA-6SD1X	317.0@1750	191.0@1750	111.5@1750	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DDI
6SD1XABEB-03★	AA-6SD1X	237.9@2200	126.0@2200	92.5@2200	738.0@1700	135.0@1700	76.6@1700	EM,TC,CAC,DDI
6SD1XABEB-04*	AA-6SD1X	227.3@1750	138.0@1750	80.6@1750	738.0@1700	135.0@1700	76.6@1700	EM,TC,CAC,DbI
6SD1XABEB-05	AA-6SD1X	335.4@2000	186.0@2000	124.1@2000	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DbI
6SD1XABEC-01	AA-6SD1X	333.1@2200	176.0@2200	129.2@2200	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,DbI
6SD1XABEC-02	AA-6SD1X	335.4@2000	186.1@2000	124.1@2000	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,DDI
6SD1XABEC-03	AA-6SD1X	335.4@1950	187.0@1950	121.6@1950	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,DD!
6SD1XABEC-04	AA-6SD1X	322.5@1800	190.0@1800	114.1@1800	991.0@1600	195.0@1600	104.1@1600	EM,TC,CAC,DDI
6SD1XABED-01	AA-6SD1X	333.1@2200	176.0@2200	129.2@2200	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DbI
6SD1XABED-02	AA-6SD1X	335.4@2000	186.0@2000	124.1@2000	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DDI
6SD1XABED-03	AA-6SD1X	322.5@1800	190.0@1800	114.1@1800	977.0@1700	193.0@1700	109.4@1700	EM,TC,CAC,DDI

*Isyzy chooses to certify models rated <215kw to the NR7 (225-450kw) standard Ref. Isuzy Ltr. DET-01-051