

KUBOTA CORPORATION

EXECUTIVE ORDER U-R-025-0083 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2002	2KBXL03.3BCC	3.318	Diesel	8000			
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
	Indirect Diesel Inje	ection	Generator Set				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS	STANDARD CATEGORY		НС	NOx	NMHC+Nox	co	PM	ACCEL	LUG	PEAK
37 ≤ KW < 75	Tier 1	STD	N/A	9.2	N/A	N/A	N/A	N/A	N/A	N/A
		CERT		6.8						

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of November 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division

lary Form Part Number Sur

KUBOTA Corporation Manufacturer:

Nonroad Cl Engine category:

2KBXL03.3BCC

EPA Engine Family:

Mfr Family Name:

Running Change Process Code:

		€ _		
Sensor Assemblies	Part Number	N/A	N/A N/A	
Sensor A	Description	N/A	N/A	
Smoke Puff	Limiter	N/A	A/N	
After Treatment Smoke Puff	<u> </u>	N/A	N/A	
Electronic Control	Module	N/A	N/A	
	Turbo Charge	N/A	N/A N/A	
	Injector	10010-53001	10010-53001	
	Injection Pump	19. Company 1 10010-53001	V3300-BG-E1 V3300-BG-E 1G517-51011 1C010-53001	V3300-BG-EZ V3500-DG-E
	Fraine Model Injection Pump	19.000 BC E	V3300-BG-E	- DO-0000
	Finding		V3300-BG-E1	V3300-BG-EZ

Cottu-R-025-0083 Running change

Part Number Sul vary Form

Manufacturer: KUBOTA Corporation

Engine category: Nonroad Cl

EPA Engine Family. 2KBXL03.3BCC

Mfr Family Name:

Process Code: Running Change

Electronic After Treatment Smoke Puff Sensor Assemblies Control Control After Treatment Smoke Puff Sensor Assemblies Control Engine Code Engine Model
- 0
- 0
– 0
– 01
– 01
– 01
- O
– 01
– 01

 E	#u	-p	-0	25	-02	8	3
 R	พทเ	ng	he	mz	ب		

Engine Model , mmary Form

KUBOTA Corporation Manufacturer:

Nonroad CI 2KBXL03.3BCC Engine category:

EPA Engine Family.

Mfr Family Name: N/A

New Submission Process Code:

Attachment

N-R-25-83

	4				. :					•
mission Control e Per SAE J1930	N.A	-AN						and the second s	andreas and the second	
9.Er Devio	10	<u>ح</u> د				- American		 and the second		
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	N/A	N/A								
7.Fuel Rate: mm/stroke@peak torque	N/A	N/A								
6.Torque @ RPM (SEA Gross)	N/A	N/A								
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)		19.8			and the second s					
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	50.6	49.2					de como en esta esta esta esta esta esta esta esta			
3.BHP@RPM	- :	51.0@1800								
anional C	V3300-BG-E	V3300-BG-E					and the second s	The state of the s		
6 6 6 9 1	1.Erigine code	V3300-BG-E2								