EXECUTIVE ORDER U-R-028-0057 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2002	2YDXL1.20D3N	1.204	Diesel	5000						
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
-	Direct Diesel Inje	ction	Crane, Loader, Tractor, Dozer, Pump, Compressor							

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION	· -			EXHAUST (g/kw-h	OPACITY (%)					
POWER · CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK	
19 ≤ KW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	20 5	15 6	50	
10 3100	7.01	CERT			8.4	5.2	0.64			7	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of November 2001.

R. B. Sammerfield, Chief

Mobile Source Operations Division

ATTACHMENT Engine Model Sur nary Form

Yanmar Diesel Engine Co.,Ltd.

Manufacturer:

Engine category: Nonroad Cl EPA Engine Family: 2YDXL1.20D3N

Mfr Family Name: N/A

New Submission Process Code:

F8 U-R-028-0057

Γ	4			-		-																		•
930 930	Ida																	>						
9.Emission Control Device Per SAE J1930									_	_	_		_			_								
ssion Per S	Ή	Ē	E	EM	II.	1	֓֞֜֞֜֞֜֞֜֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֡֓֓֡֓֡֓֡֓֡֓֡֓֡	ב טוני	ן וע	Σ	∑ W	Ξ	Ξ	Ш	∑ LL	2	֓֞֞֞֞֞֞֞֓֞֓֞֓֞֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	IJ Z	- 1					
J.Emi														,					- 1					
									ļ															
8.Fuel Rate: (lbs/hr)@peak torque																								
8.Fuel Rate: hr)@peak to	7.9	7.1	7.1	~	6	2 6) i	2	8.9	ω Ο	7.0	6.9	7.0	0.7	5	2 6	2	0.						
Fue or)@F		-		_		Ĭ,			_		•					1								
(Bost						: 1																		
¥																								
7.Fuel Rate: mm/stroke@peak torque	O	6	0	ے (, ,	.	4	4	4	4	4	7	œ	4		, .	4	4						
7.Fuel Rate: n/stroke@pe torque	24.9	23.9	22.0	22.0	3 8	43.4	23.4	23.4	24.4	24.4	23.4	23.2	23.6	23.4	3 6	5.5.3	4.5.4	23.4						
7.F nm/sl																			ME					
_																								
∑	C	ے ا	ء ا د))	2 6	2	오	0	오	2	2	g	2	۶	2 9	2	2	ഉ						
6.Torque @ RPM (SEA Gross)	57 4/1920	57 0/1800	57 0/4 BOO	000000000000000000000000000000000000000	77	56.5/1800	56.5/1800	56.5/1800	57.6/2200	57.6/2200	56.5/1800	56.0/1800	57.4/1800	58 5/1800	5 3	0001/6.00	56,5/1800	56.5/1800						
irque SEA (7.4	0		ָ ט ע	ָרָ מַן	56.5	56.5	56.5	57.6	57.6	56.5	56.0	57.4	2) (ဂ္ဂ	56.5	56.5						
6.Tc																								
•																								
5.Fuel Rate: (bs/hr) @ peak HP (for diesels only)																			0.000					000 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
5.Fuel Rate: bs/hr) @ peak Hi (for diesels only)	11.2	. C		0.0	7.0	2	10.1	10.1	12.6	12.6	101	66	101		2	9	10.1	5.						
5.Fu s/hr) or die		`					Ì									1							88.3	
<u></u>										71,									18.8					
F.																								
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	1	- (ן מ		ဖွ	4	4	4	o	0	7	· -	Jo	۰ ا ز	4	4	4	4						
4.Fuel Rate: itroke @ pea or diesel only	5	· · · · ·	6.22	8.22	20.6	20.4	20.4	20.4	24.0	24.0	20.4	20.1	2 2 0	,	20.4	20.4	20.4	20.4						
4.F Vstro (for a								24 00 0 100 0 0 100 0 0 0 0											1111				300	
Ē							:					1000							3000				1363	
∑ :		_		0		0	0	0	0	ے ا	, ,) c		 - C	0	٥	0	g						
3.BHP@RPM		27.7/3200	26.4/2800	26.4/2800	27,3/3000	27,0/3000	27.0/3000	27.0/3000	28.9/3200	0025/0 80		26 6/3000		23.11.2000	27.0/3000	27.0/3000	27.0/3000	27 0/3000						
BHP.	1 1	;;	6.4/	6.4	7.3	7.0	7.0	7.0	80	0	֓֞֞֜֞֜֞֜֞֜֞֜֜֞֜֜֜֜֜֜֓֓֓֓֓֓֓֓֓֜֜֜֜֝֓֓֓֓֓֓֓֜֝֓֓֓֜֜֝֓֓֓֜֝֓֡֓֜֝֡) (C	֓֞֞֜֜֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֓֓֓֓֡֓֡֓֡֓	0	27.0	27.0	27 0	27.0	?					
بن ج	-	N '	7	7	7		.,		``			` `]			•								
_	.		11.		_										-	4	4	۵	-		. :			
Chaine Model		3TNE78A-EDM	3TNE78A-ERJF	3TNE78A-ERJ	3TNE78A-EHP	3TNE78A-ESA	可	3TNE78A-EJS	ATNEZ8A-F.IF) II	CH-COLUMNIC	31NE/8A-EYA	いうはくのとはつつ	31NE/8A-EBE	3TNE78A-ESA	3TNE78A-ESA	3TNF78A-ESA	STAISTRA ESA	֝֝֝֝֝֝֝֝֝֝֝֝֡֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֡֓֓֓֓֓֡֓֡֓֓֡֓					
2	<u> </u>	8A-I	8A-E	₩,	.¥8′	₹8	3TNE78A-EJ	78A	A87	0 0	5		5	\$	78A	78A	78A	Var	5					
	5	일	Ę7	빌	NE7	Ä	Z	빌	L Z			뷘		빌	쀨	뿔	Ä	֓֞֝֟֝֟֝֟֝֟֝֟֝֟֝֟֝֓֓֓֟֟֝֟֝֟֝֟֝֓֓֓֓֟֝֟֝֟֝֟֝	<u> </u>					
C TI	7.7	31	31	3	3	37	က	3	7	ָ ק	າ ¦	 	~	<u>ب</u>	8	3	٦.	, [اد					
٥	<u>u</u>																1							
,	3			-																				
	Jime	₹	A/N	¥ Z	۲	X	\X	4 Z		2 3	₹ 2	ĕ :	۲ Z	∢ Ž	₹ Z	A/Z	N/N	2 2						
	1.Engine coue	_	_	_	_						;:													
-	-	. j			ĺ	1				- .			1			į.	ļ :	: -		1.	1	<u> ' :</u>		<u> 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1</u>