New Off-Road Compression-Ignition Engines



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2002	2ICLL1.12B3G	1.124	Diesel	3000				
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION					
	Indirect Diesel Inje	ection	Tractor					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION			E	XHAUST (g/kw-l		OPACITY (%)			
	STANDARD CATEGORY		HC	NOx	NMHC+NOx	ÇO	PM	ACCEL	LUG	PEAK
8 <u><</u> KW<19	Tier 1	STD	N/A	N/A	9.5	6.6	0.80	20	15	50
		CERT			5.6	1.4	0.37	10	5	12

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

R. B. Summerfield, Chief

Mobile Source Operations Division

ATTE HMENT 1 OF 1

•

ISEKI MATSUYAMA MFG. CO., LTD. Manufacturer:

Nonroad Cl Engine category:

EPA Engine Family: 2ICLL1.12B3G

4-038-000H

Mfr Family Name: NONE

New Sub - continued Process Code:

_	1		NE.										TEN.		P (
9.Emission Control Device Per SAE J1930	95		4.			8.75	47.7	1.4				1 to 1			٠.
눌	-							1.5							
2 8	300									N 44	13.74 J	12 -446 13:446			
sion er S	Ī	正	2,3												
niss P.e	10.47			17.7						12.4	3.7				
ři sš				- 1							93.4				
9 De				17.	1472 d 1572 d							_ ivi			
Đ.		ĺ			1				1.77 mg			V		2	
15	4	4		13.5°	1.54				1314				E%.]	3	
ate ≿ r	Ö	Ö				19.5 25.									
Pea bea	Ö	Ö											4.4		
8.Fuel Rate: (lbs/hr)@peak lorque	4	8.4@50.4											127		
.8 /}}.	æ	æ				1	2						1.34	1	
SQ)				Total i	1.2	5,1/1					200	2	Max :		
												n -	N.C.		
7.Fuel Rate: mm/stroke@peak torque	4	4			<u></u>						Ap. X			E	
age Go	20	20		56.	, i				845			E&F	i Eu		
uel Rat troke@ torque	25.0@50.4	25.0@50.4		1 a 7 (2) 1 to 1	1.54		E-AS F-S-F	100 A				174.0			
곮 캶	5.0	5.0							14700 14700		1000	23		1.26	į
7. Jm/	N	N		27					ight.				5-1		
=	No.		.a .s				25.	- Bed			100 mg	ión ¿			
											7. K.		File		
≨	0	0		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			-4 %			10.001					
RF (SS)	8	8	. Frie				117.7 117.3			L., 5		Hay I			
6.Torque @ RPM (SEA Gross)	50.4@2000	50.4@2000		100					목걸	Teff.			irs.		
and S	4.	4	× .	# W							(2.50) (3.50)	talen.			
Tor (SE	50	20										1 30% 14 5a			
G			1327 7134					1		TEM.	ĐÝ.	12			
				17.11	15.4	1277	10 A 10 10 A	- P		3.00		1.4			
₽∼					1.7			- 34	10265 10365				7 Se 7		
or k të	(C)	6	4.7		. ::				N. 14.19 1. 1527			12 %			
Ra pe sis	32	22	, 11												
es © se	9	10.6@23.3			1 70		6,1	F -5	inger Editori		7.7	9/61			
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	10.6@23.3	5					1.33						lyn. F	Lat l	
(<u>(</u>		. :	. 4	12.5	1						建 构		177		
_					2 149 1 2 3 14						Ž.	1 100	563		
先	• •	:	F. 11	17	. "								P. Cart	130	
:; ≩ <u>₹</u>	33	33			1 -1							12.0	[35]		
Sat Pe Pe	22	8	3.	la de			w.		4.5	1.19	10 MIN .				
4.Fuel Rate: //stroke @ peak (for diesel only)	99	22.6@2			1.24	62	2.5		1		(Va.)	.7	1,00		
도중합	χį	χį	£ :				54.3							100	
4.Fuel Rate: mm/stroke @ peak (for diesel only)	22.6@23.3		.; ¹ = .	500			1				271		2	E.	
Ē						- fig. I	72.1		N 4431	4.5		1374			
			/*· :	1.2	75	- k			i phu	* * .	61		: Grad		
≅ ?	8	2							2.7	1.14	15	Si.	4 *		
3.BHP@RPM (SAE Gross)	23.3@2800	23.3@2800			4	12.					181 1844 (1		1004		
9 © O	0	<u>(a)</u>		i i kanasi			F. 67		4						
SA BH	3.3	رب دن			1280		10.000 10.000		1984 Mills 1987 198				11/2		
	N	Ŋ		į.		- 24	1 m			7.			\$		
	E3112 03 per								8-0	45	52.43	微点			
- 	4.54 4.55								2 Add		0.4				
ğ				1.41.01	, A	Ü,	e green		16.4.4	F Z NE			******		
Ĭ	7	0			- 1				1,444			1 10 2		1	
<u> </u>	-	17							£ 1, 4, 5					94 m 4	
2.Engine Model	EL .	E3112G			,		× 3:	. 1					10	į į	
ய்					-		i de la companya de l						s Ale Page Nac		
2				# 7 # 2 1 2 # 3 1 2 # 3 1 2			- Ga				****		15.4		
				1.7					J. 1		. Se			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
de	- 1			PA H			1,80,1 1,73				***	1	20		
ပိ				1.5										1.	:
ē	4	⋖		11.50							1-32		N. N.	1 -	
gi	N/N	Ż	· . · · .				±.			- 28	Nat	133	irgi .		
1.Engine Code		Y N		1 12											
←					:					///					1
					<u> </u>										