Cummins Inc.

EXECUTIVE ORDER U-R-002-0169

New Off-Road
Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2003	3CEXL0359ACA	5.9	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection			Forklift			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD	EXHAUST (g/kw-hr)				OPACITY (%)				
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	РМ	ACCEL	LUG	PEAK
37 <u>&lt;</u> KW < 75	Tier 1	STD	N/A	9.2	N/A	N/A	N/A	20	15	50
		CERT		8.5				2	2	5

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

<del>----</del>

day of November 2002.

Allep Lyons, Chief

Mobile Source Operations Division

## Engine Model Summary Form APIAGIMENT रिट्टे । ०२।

U-R-002-0169

Manufacturer: Cummins Inc.

Engine category: Nonroad Over 50 Hp

EPA Engine Family: 3CEXL.0359ACA

Mfr Family Name: A401

Process Code: New Submission

_	4
8.Fuel Rate: 9.Emission Control lbs/hr)@peak torque Device Per SAE J1930	
Cont	ΣΣ
ion (	ш ш
miss e Pe	DDI,EM DDI,EM
9.Er	
۵	
. <u>D</u>	
tate:	29.3 26.5
per F	29.3 26.5
8.F.	
/sql)	
7.Fuel Rate: mm/stroke@peak torque (It	
e: Peat	
Rat e@l	4 以
Trok Trok	n) d)
7.5 Symr	
=	
~	
RPA SS)	88
@ <u>@</u>	(a) (b)
6.Torque @ RPM (SEA Gross)	255@1600 246@1500
6.To	o o
∓ <del>∑</del>	
tate: eak s on	4 0
5.Fuel Rate: /hr) @ peak or diesels on	37.4 35.3
5.Fuel Rate: lbs/hr) @ peak HP (for diesels only)	
~	
k HP	
4.Fuel Rate: troke @ pea or diesel only	တတ
ke (	ਧਾ
4.F /stro (for	
Ē _	
P. (8)	20
General Green	22.22
3.BHP@RPM (SAE Gross)	<b>@</b> @
3.E	98 @ 2250 93 @ 2150
<del>©</del>	
<b>Q</b> Q	
<u>.</u> ≥	)-6 )-6
űġ	85.9-C B5.9-C
2.Engine Model	
N	*
1.Engine Code	96 98
Ö	20 20
ine	;FR90499; ;FR90498
<u>g</u> n:	38;F 37:F
<del>т.</del>	255
	w