

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)	
2003	3CEXL0359ABC	5.9	Diesel	8000	
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION		
Direct Dies	sel Injection, Turbocharg	er, Charge Air Cooler	Crane, Loader, Tractor, Dozer, Pump, Compressor		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
CLASS	CATEGORY		НС	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
75 ≤ KW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
130 ≤ KW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		CERT			5.7	0.9	0.18	19	1	41

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

12 17

_ day of November 2002

Allen yons, Chief

Mobile Source Operations Division

Engine Model Summary Form ATMACHMENT ですしゃもし

Engine category: Nonroad CI

Manufacturer:

Cummins Inc.

EPA Engine Family: 3CEXL0359ABC

Mfr Family Name: C403

Process Code: **New Submission**

U-R-002-0172

			~ "		NN NN	
8276;FR9923	8265;FR9903 8266;FR9904	8105;FR90997	8111;FR9100	8111;FR90649	2846,FR90652 2678;FR90650	in.
6	<u> </u>	ä	邿	Ť.	8 S	l.Engine Code
# . .	热波	H9	89	89	B9 B9	e e
, ĕ	90	360	Ø	8	36 36	ပ္ပ
ω	ω <u>4</u>	77	Ξ.	9	ÖK	de
P. W.						
	44					ĪŪ.
B	異思	85	85	띯.	88 88	gi.
B5.9-C	B5.9-C	B5.9-C	B5.9-C	ဖ္	B5.9-C	ह
େ	0.0	O	О	C	O O	2.Engine Model
		Ħ.				<u>e</u>
_		_	1	_	يدايد.	_ 3
115@2300	128@2000 140@ 2000	66	145@2200	178@2000	189@2050 150@1950	3.BHP@RPN (SAE Gross)
(Q)	(e) (e)	10	(A)	(9)	(D) (D)	ල් මි ල්
30	8 8	95(Š	9	95(APN oss)
, O	00	۲	Ο.	٦		
I i						3
						4.Fuel Rate: mm/stroke @ peak HP (for diesel only)
		P.				or tree. E
64	ω. _Σ	100	78	99	84 <u>-</u> 2	4.Fuel Rate: /stroke @ peak (for diesel only)
		0	I ~	Ī		pe onl
		1.			, , ,	S # I
788		1				ס
						⊋ g
						5.Fuel Rate: bs/hr) @ peak H (for diesels only
49	54.5 64.5	65.8	58.2	66.5	69.6 55.3	98.9 19.00
iM	တ် ဖ) ¦œ	N	Ċ	ယတ	tate beal
į Ž						5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)
100	7 4					6.1
35	46	49	4	:83	547@1500 460@1500).Torque @ RPM (SEA Gross)
විද) 6		8	<u>```</u>	A [6
1 3	<u> </u>	. 6	5	运	5 5	о R Sson
€ 1	3,8,8	3∥5	18	ಠ	ಕಕ	PK
	114			H		
						₹
				b		7.⊢ı π/stı 1
	188	o =	82	190	8 5	uel Ra troke@ torque
4	⊾ w c	° R	; N	ō	, O) &	7ruel Hate: mm/stroke@peak torque
						eak
				l.		<u>_</u>
		F				bs/h
ý	3 43 6) 1 2	1 <u>4</u> 3 5	50.4	43.6	8.Fuel Rate: hr)@peak to
-	. O (רו ת	. 0			k be
						que
1				H		D ~
i, c	יַ פַ כַ	2 5	2 ⊆	2 5	걸모드	9.Emission Control bevice Per SAE J193
<u> </u>	יַ בַּי	<u>ַ</u>	á l≟		íšŧ	niss Pe
	3 B	3 8	۶ c	i c	$\circ \circ \circ$	ξ g
4 4					DDI, TC,CAC	μ Ligh
18° 1) O) () C) C) O	8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930
1		-1	41			. 0
				and the	20 July 2000	<u>468</u>