

## LIEBHERR MACHINES BULLE SA

EXECUTIVE ORDER U-R-018-0039 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours) 8000			
2003	3LHAL9.96AUA	6.6 and 10.0	Diesel				
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
Direct Dies	sel Injection, Turbocharg Engine Control Mo	er, Charge Air Cooler, odule	Crane, Loader, Dozer, Compressor				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD			E	XHAUST (g/kW-	OPACITY (%)				
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
225 ≤ kW < 450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	20	15	50
		CERT			6.2	0.7	0.16	5	2	11

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

Manufacturer: Liebherr Machines Bulle SA

Engine category: Nonroad Cl

EPA Engine Family: 3LHAL9.96AUA

Mfr Family Name: NA

Process Code: New Submission

ATTACHMENT

U-R-018-039

	4						37		10735				
ol 930	ပြု												
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	NA DD NATTO, CAC, EC	2,1						79.2	N. 45				
ion C r SA	Q ₹			355								100	
nissi 9 Pel	5 5		\$9.5		\$				60.0				
9.En	AT.				Selfibr Sulkisia								
۵				130			- Şr	1941. 1943.4	*				
orduk	2				5							â	1.0
8.Fuel Rate: hr)@peak to		diam'r.											
uel F	2												100
8.F /hr)(								10261A 41, 40,2					
sqı)				***	.:01 .5.344								
*			3.0										
ate:	217						ew.						
7.Fuel Rate: mm/stroke@peak torque	252@1217		45 35 8 34 35				1.5						
7.Fu n/stro to	252	.,			, d				0.45 (4.1		-  -		177
. E	3.6 38		15 %		300								
	18.A.		Ž.	32.		134						1.7.1	
PM ₩	1217@1200-14 50				488								
6.Torque @ RPM (SEA Gross)	9120				194				. 70				
que SA G	@ ~					100 A							
.Tor	2		24										
9	<b>S</b>		\$ 1 \$\delta\$				8.50 8.50						
유 🤝													
ate: sak F only		177972		5 34	18° 1		43.5		E NEEL E NEEL E NEEL				
a Ra	NA	100						6 (V) - 1 5 (0 ) - 1					
5.Fuel Rate: (bs/hr) @ peak HP (for diesels only)				2.4									(\$4.4)
(fol)		7.55K.) 7.54K.)		138								1,3	
윺			Sold Sold							i i	i		200 T
~ ~	2												
Rate 19 pe	936		[3.5] [3.5]		Entransación de la constantidad			100 M					
4.Fuel Rate: stroke @ peal or diesel only	92@			975				Ý.,					
4.Fuel Rate: mm/stroke @ peak (for diesel only)	192@367											1.1	
E C			37.5				1998   1880						
							A		1000				
(PM	8												1
@ G	95,					25							
3.BHP@RPM (SAE Gross)	)29									. !			
2.Engine Model 🎎	2		1364										
ode	934				-5-								
Ž	끝					1 V.		\$ 7 \$ 7 \$ 7	. A				
giile	926						53						
يَّقَ	ă												
2.							3.4						
<u> </u>													
Š							3				1 1		
ne (	≰		253K)								i		
1.Engine Code		17				1.02							100 m
<u></u>	NA D926TI-E 274 367@2100										1		
	245 1		1,10			Elid_	_ 1::::1	\$ X		<u>i:</u>	<del>`</del> <del>'</del>	<u> </u>	paga, e a Cal