



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2003	3L5XL1.86FTC	1.86	Diesel	5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger			Pump, Compressor, Generator Set	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	N/A	N/A	N/A
		CERT	--	--	8.1	2.8	0.66	-	-	-

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 7TH day of January 2003.

Allen Lyons, Chief
Mobile Source Operations Division


Engine Model Summary Form

Attachment 1 of 1

41-R-623-0015

Manufacturer: Lister-Petter
 Engine category: Nonroad CI
 EPA Engine Family: 3L5XL1.86FTC
 Mfr Family Name: LPWT4
 Process Code: New Submission

50 State Code	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
	LPWT4	308	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM 7c, 80F
	LPWT4	358	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
	DNAF	374	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
	LPWT4	379	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
	LPWT4	380	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
	LPWT4	307	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM
	LPWT4	357	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM
	LPWT4	381	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM



Engine Model Summary Form

Attachment 1 of 1

41-R-623-0015

Manufacturer: Lister-Petter
 Engine category: Nonroad CI
 EPA Engine Family: 3L5XL1.86FTC
 Mfr Family Name: LPWTA
 Process Code: New Submission

50 State Code	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
LPWTA		308	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM 7c, 8c
LPWTA		358	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
DNAF		374	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
LPWTA		379	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
LPWTA		380	35.1 @ 1800	35	14.0	N/A	N/A	N/A	EM
LPWTA		307	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM
LPWTA		357	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM
LPWTA		381	28.3 @ 1500	34	11.1	N/A	N/A	N/A	EM

