

ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0063 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2003	3H3XL1. 49N3C	1.496	Diesel	3000			
SPECIAL.	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
	Indirect Diesel Inje	ction	Generator				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD				EXHAUST (g/kw-l		OPACITY (%)			
CLASS	CATEGORY		нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
8 <u><</u> KW<19	Tier 1	STD	N/A	N/A	9.5	6.6	0.80	N/A	N/A	N/A
		CERT		-	7.2	1.6	0.39			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of January 2003.

Allen Lyons, Chief

Mobile Source Operations Division

ATTACHMENT I OF !

Engine Model Summary Form

U-R-026-0063

Manufacturer: Ishikawajima-Shibaura Machinery Co., Ltd.

Engine category: Nonroad Cl

EPA Engine Family: 3H3XL1.49N3C

Mfr Family Name: N/A

Process Code: New Submission

LEgine Code 2 Engine Model 3 Engine Model A Fuel Rate: Sriel Rate: Teach Rat		4		- ***		. V	T.,		A Section		: * P		, me e e e e e e e e e e e e e e e e e e	erie op 57 Line og		•
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>930 930</th> <th></th>	930 930															
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>Contr F J1</th> <th></th>	Contr F J1															
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>ion (sr SA</th> <th>正</th> <th>旦</th> <th>旦</th> <th>正</th> <th>旦</th> <th>드</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	ion (sr SA	正	旦	旦	正	旦	드									
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>miss e Pe</th> <th></th>	miss e Pe															
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>9.E Jevic</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>1.</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	9.E Jevic							1.								
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>ne L</th> <th></th>	ne L															
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>fe: torq</th> <th></th>	fe: torq															
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>if Ra oeak</th> <th>₹ Ş</th> <th>Ϋ́</th> <th>₹/A</th> <th>٩</th> <th>Ϋ́</th> <th>¥,</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	if Ra oeak	₹ Ş	Ϋ́	₹/A	٩	Ϋ́	¥,									
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>.F.u.</th> <th>-</th> <th>_</th> <th>_</th> <th></th> <th>_</th> <th>_</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	.F.u.	-	_	_		_	_									
2. Engine Model 3.BHP@RPM (SAE Gross) mustrake @ peak HP (rof desets only) 5. Fuel Rate: (rof desets only) 5. Fuel Rate: (rof desets only) 7. Fuel Rate: (rof desets only) <th>B Wyg</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th>and and and and and and and and and and</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	B Wyg									and						
2.Engine Model 3.BHP@RPM (sAE Gross) mm/storde gpeak HP (tshr)/gpeak HP (sEA Gross) 6.Torque @ RPM (scross) KE18/1500C 17.7@1500 30.74/-1.8 7.84/-0.4 N/A KE21/1800C 21.3@1800 30.74/-1.8 7.84/-0.4 N/A HL18/1500C 21.3@1800 30.74/-1.8 9.14/-0.5 N/A 20/1800C 20.1@1800 30.24/-1.7 7.24/-0.4 N/A 20/1800C 20.1@1800 30.74/-1.8 9.14/-0.5 N/A 21/1800C 20.5@1800 30.74/-1.8 9.14/-0.5 N/A																
2.Engine Model 3.BHP@RPM (sAE Gross) mm/storde gpeak HP (tshr)/gpeak HP (sEA Gross) 6.Torque @ RPM (scross) KE18/1500C 17.7@1500 30.74/-1.8 7.84/-0.4 N/A KE21/1800C 21.3@1800 30.74/-1.8 7.84/-0.4 N/A HL18/1500C 21.3@1800 30.74/-1.8 9.14/-0.5 N/A 20/1800C 20.1@1800 30.24/-1.7 7.24/-0.4 N/A 20/1800C 20.1@1800 30.74/-1.8 9.14/-0.5 N/A 21/1800C 20.5@1800 30.74/-1.8 9.14/-0.5 N/A	te: peak															-
2.Engine Model 3.BHP@RPM (sAE Gross) mm/storde gpeak HP (tshr)/gpeak HP (sEA Gross) 6.Torque @ RPM (scross) KE18/1500C 17.7@1500 30.74/-1.8 7.84/-0.4 N/A KE21/1800C 21.3@1800 30.74/-1.8 7.84/-0.4 N/A HL18/1500C 21.3@1800 30.74/-1.8 9.14/-0.5 N/A 20/1800C 20.1@1800 30.24/-1.7 7.24/-0.4 N/A 20/1800C 20.1@1800 30.74/-1.8 9.14/-0.5 N/A 21/1800C 20.5@1800 30.74/-1.8 9.14/-0.5 N/A	Re@ que	₹ Ş	Ϋ́	4	ξ	۷/A	Ş									
2.Engine Model 3.BHP@RPM (sAE Gross) mm/storde gpeak HP (tshr)/gpeak HP (sEA Gross) 6.Torque @ RPM (scross) KE18/1500C 17.7@1500 30.74/-1.8 7.84/-0.4 N/A KE21/1800C 21.3@1800 30.74/-1.8 7.84/-0.4 N/A HL18/1500C 21.3@1800 30.74/-1.8 9.14/-0.5 N/A 20/1800C 20.1@1800 30.24/-1.7 7.24/-0.4 N/A 20/1800C 20.1@1800 30.74/-1.8 9.14/-0.5 N/A 21/1800C 20.5@1800 30.74/-1.8 9.14/-0.5 N/A	Fue/stro	-	_	_	_	-	_			111.111						
2.Engine Model 3.BHP@RPM (sAE Gross) mm/storde gpeak HP (tshr)/gpeak HP (sEA Gross) 6.Torque @ RPM (scross) KE18/1500C 17.7@1500 30.74/-1.8 7.84/-0.4 N/A KE21/1800C 21.3@1800 30.74/-1.8 7.84/-0.4 N/A HL18/1500C 21.3@1800 30.74/-1.8 9.14/-0.5 N/A 20/1800C 20.1@1800 30.24/-1.7 7.24/-0.4 N/A 20/1800C 20.1@1800 30.74/-1.8 9.14/-0.5 N/A 21/1800C 20.5@1800 30.74/-1.8 9.14/-0.5 N/A	7 mm					:-										
2. Engine Model (SAE Gross) mmstacke@ peak HP (Ibsh/10) greak HP (Ishn/10) greak HP (Ishn										To the same of the						
2. Engine Model (SAE Gross) mmstacke@ peak HP (Ibsh/10) greak HP (Ishn/10) greak HP (Ishn	PW (s															
2. Engine Model (SAE Gross) mmstacke@ peak HP (Ibsh/10) greak HP (Ishn/10) greak HP (Ishn	@ R Sross	⋖	⋖	4	⋖	∢	⋖									
2. Engine Model (SAE Gross) mmstacke@ peak HP (Ibsh/10) greak HP (Ishn/10) greak HP (Ishn	que EA (Z	z	Z	Z	Z	Z			موسونان.						
2. Engine Model (SAE Gross) mmstacke@ peak HP (Ibsh/10) greak HP (Ishn/10) greak HP (Ishn	S.Tor									THE STATE OF THE S	-					
2. Engine Model (SAE Gross) (for diesel only) (Gr diesel only) (BE18/1500C 17.7@1500 30.7+/-1.8 (BE21/1800C 21.1@1800 30.7+/-1.8 (BE21/1800C 21.7@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20																
2. Engine Model (SAE Gross) (for diesel only) (Gr diesel only) (BE18/1500C 17.7@1500 30.7+/-1.8 (BE21/1800C 21.1@1800 30.7+/-1.8 (BE21/1800C 21.7@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20	ΞĒ								AND MANUEL AND ADDRESS OF THE PARTY.							
2. Engine Model (SAE Gross) (for diesel only) (Gr diesel only) (BE18/1500C 17.7@1500 30.7+/-1.8 (BE21/1800C 21.1@1800 30.7+/-1.8 (BE21/1800C 21.7@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20	kate: seak s on	0.4	-0.5	0.4	0.5	-0.5	0.5			nine many					1	
2. Engine Model (SAE Gross) (for diesel only) (Gr diesel only) (BE18/1500C 17.7@1500 30.7+/-1.8 (BE21/1800C 21.1@1800 30.7+/-1.8 (BE21/1800C 21.7@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20	uel F @ F esel	(+/9	1+/	2+/)+O	1+/	+				2					
2. Engine Model (SAE Gross) (for diesel only) (Gr diesel only) (BE18/1500C 17.7@1500 30.7+/-1.8 (BE21/1800C 21.1@1800 30.7+/-1.8 (BE21/1800C 21.7@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.1@1800 30.7+/-1.8 (BE21/1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20.5@1800 20.7+/-1.8 (BE21/1800C 20.5@1800C 20	5.Fi s/hr) or di	7	9.	7	о. С	6	9			-						
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	ق ج															
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	웊					•				1						
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	ate: peak only	1.8	1.8	1.7	4.8	1.8	1.8									
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	el Re	7+/-	-/+/	2+/	2+/-	7+/	7+/-		.55							
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	4.Fu troke or die	30.	30.	29.	30.	30.	30.									
2.Engine Model (SAE Gross) KE18/1500C 17.7@1500 HL18/1500C 21.1@1800 20/1800C 20.1@1800 21/1800C 20.5@1800	mr/s)			4-												
2.Engine Model KE18/1500C KE21/1800C HL18/1500C HL22/1800C 20/1800C 21/1800C	=															
2.Engine Model KE18/1500C KE21/1800C HL18/1500C HL22/1800C 20/1800C 21/1800C	PM (ss	8	8	8	8	00	8									
2.Engine Model KE18/1500C KE21/1800C HL18/1500C HL22/1800C 20/1800C 21/1800C	@ G	315	918	315	3018	2018	318									
2.Engine Model KE18/1500C KE21/1800C HL18/1500C HL22/1800C 20/1800C 21/1800C	BHP SAE	7.7	1.1	3.1(1.7	0.1).5(4			
	_د ن ع	1	5	3	2	7	7									
	ade	ပ္	ပ္က	ပ္က	ပ္က					1						
	Ž	200	8	500	8	8	90			, , ,						
	gine	18/	111	8/1	27	118	/18									
	ĒΪ	A A	A A	Ή	呈	50	21									
1.Engine Code 103-15 103-15 403C-15 403C-15 N843-2 N843-C	2		_	-						445-44		4		1 - 1		
1.Engine Co 103-15 103-15 403C-15 403C-15 N843-C	de		1													
1.Engine 103-1 103-1 403C- 403C- N843	ပိ	5	5	15	15	7	ပှ					and a distance of the				
1.En	yine	33-1	33-1	30	36-	343	343									
	Enc	16	1	40	40	ž	ž									
						ļ					<u> </u>					