## ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0070 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2003	3H3XL1.33J84	1.33	Diesel	5000					
SPECIAL F	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
	Indirect Diesel Inje	ection	Tractor and Industrial Equipment						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD			I	OF	OPACITY (%)				
CLASS	CATEGORY	STD	HC N/A	NOx N/A	NMHC+NOx	<b>CO</b> 5.5	PM	ACCEL	LUG 15	PEAK
19 <u>&lt;</u> KW<37	Tier 1				9.5		0.80	20		50
		CERT			5.5	1.6	0.38	5	7	12

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of January 2003.

Aller Lyons, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

## ATTACHMENT 10F1

Manufacturer: Ishikawajima-Shibaura Machinery Co., Ltd.

Engine category: Nonroad CI

EPA Engine Family. 3H3XL1.33J84

Mfr Family Name: N/A

Process Code: New Submission

U-R-026-0070

_	1,	:.	٠	· .			· .								- (			•
nission Control Per SAE J1930	묘	正	드	田	旦	E.	E	IFI	F					Andreas of the state of the sta				
9.Em 3 Device																		
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930	10.2+/-0.5	10.2+/-0.5	9.8+/-0.5	10.8+/-0.7	10.8+/-0.4	9.7+/-0.6	10.7+/-0.6	9.7+/-0.6	10.6+/-0.6		Application transmission and property to the control of the contro				and the state of t		AND THE RESERVE AND THE RESERV	
7.Fuel Rate: mm/stroke@peak torque	28.2+/-1.4	28.2+/-1.4	29.8+/-1.5	28:6+/-1.9	31.3+/-1.2	29.4+/-1.9	32.5+/-1.8	29.4+/-1.9	32,3+/-2.5								A CARLO CARL	
6.Torque @ RPM (SEA Gross)	57.1@2200	57.1@2200	57.2@2000	57.9@2300	62.1@2100	60.6@2000	65.1@2000	60.6@2000	65.1@2000									
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	12.2+/-0.8	13.1+/-0.9	12.1+/-0.5	13.2+/-0.8	12.3+/-0.5	10.9+/-0.6	12.7+/-0.8	10.9+/-0.6	12.7+/-0.8						A do the beautiful and the million of the beautiful and the second of th			en grannen om federmålske kodistalskater (spriver av te kommen ommen
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	26.5+/-1.8	26.5+/-1.8	28.3+/-1.2	26.7+/-1.7	27.7+/-1.2	25.5+/-1.4	27.5+/-1.6	25.5+/-1.4	27.5+/-1.6						. Per angar apara anno anno anno anno anno anno anno a	The second secon		and the set before the country of th
3.BHP@RPM (SAE Gross)	28.0@2800	28.0@3000	27.4@2600	30.0@3000	27.9@2700	24.9@2600	29.0@2800	24.9@2600	29.0@2800				And the state of t				Andreas and the second	
2.Engine Model	KH28/2800	KH28/3000	27/2600-F1630	30/3000-CM	28/2700-CM	TC25/2600	TC29/2800	TC25/2600	TC29/2800					en e		and the state of t		
1.Engine Code	103-13	103-13	J843-2	J843-2	J843-3	J843-3	J843-3	J843-4	J843-4					And the second of the second control of the second of the				