YANMAR CO., LTD.

EXECUTIVE ORDER U-R-028-0119 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2003	3YDXL1.50D3T	1.496	Diesel 5000							
	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION							
l	Direct Diesel Injection, To	urbocharger	Crane, Loader, Tracto Dozer, Pump, Compres							

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION		·	E		OPACITY (%)					
	STANDARD		нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK	
19 ≤ kW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	20	15	50	
		CERT			8.7	2.1	0.65	7	4	16	

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2002.

Allen Lyons, Chief

Mobile Source Operations Division

## Engine Model S mary Form

Manufacturer: Yanmar Co., Ltd.

Engine category: Nonroad CI

EPA Engine Family: 3YDXL1.50D3T

Mfr Family Name: N/A

Process Code: New Submission

ATTACHMENT

ED U-R-028-0119

		vie v	3.25. 3.15.		7.	-							O.S.	30				() ×		7.4	52.	影	i) in			
9.Emission Control Device Per SAE J1930	<	EM DDI,TE									\$ 47.	٠,	. X			- - -										
9.Emission Control evice Per SAE J193	EM	aa.	3,7	, _				: 1		:		25 - 1		4.	(0) (3)				***							
sion er S	E	EM	EM	EM	173 244					1400 t	11.20	1.4.1			74	1	1 A				* (*)					
Emis ice P				.: 			4		ж.	:					.) A		23	: - : : : : : : : : : : : : : : :								
o Oev		1				d.	2.5			. :-							7.X						, 1 1 1 1	34	1	
que							Nice Also	-	X.:					祕.	1837) (2)			# + 2 2 .								
8.Fuel Rate: (lbs/hr)@peak torque	ထ	m	8	ထ	\$1.5 \$1.5				**************************************		3 a 3				: ::::::::::::::::::::::::::::::::::::				.5	# 14 1						
8.Fuel Rate: hr)@peak tot	10.8	10.8	10.8	10.8	14.5°	132					3.0															
8.F.					( ) ( )									TO SE			÷									
sq))				- :	3				7. 14.		44 C	1 1	1.49	j.	200 V 201					7 } .	37.	-				
*			•										1-4 1-3						, * , * , * , *							
tate: @per	က	2	2	2		. P.		:	,	1.			1,312	: - '	100				- P				33			
7.Fuel Rate: n/stroke@pe torque	36,3	36.2	36.2	36.2					77					- 7 - 4					5.5						6	
7.Fuel Rate: mm/stroke@peak torque	54								.55				1.51						等							
E			-? 3-€	; 1 i		in el Hari	: :: :: :: :: :: :: :: :: :: :: :: :: :			1 J		-	\$ \bullet \( \text{\ti}\text{\texi{\text{\texi}\text{\text{\tex{\text{\texit{\text{\texi}\text{\texi}\titt{\text{\texit{\text{\texi}\text{\texi}\text{\texi}\text{\texi{\texi{\texi{\texi{\texi}							11.7	0.7		100	- 71.	Ž.	
⋝	B 7.									72	***	11.	- A				17.00 30.00			. 1-1 . 1-1			1,000			
6.Torque @ RPM (SEA Gross)	88.5/1800	88.0/1800	88.0/1800.	88,0/1800	500	4.					<b>5</b> 5								54.6°						<b>A</b>	
forque @ RP (SEA Gross)	5/1	0/1	0,1	0/1		3.															: ::::				*	
Torqi (SE/	88	88	88	88					1.5							 			19 66 18 64		7. 24.					-
ဖ်											×		1.73	4.			3 . 3 .3									
₽ ←			1	:	4.70						3.		- 47		Ę.		2		7				138		æ	
ak F only						10						4.														
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	16.7	16.4	16.4	16.4	¥ 	*** = 1		·				-:	1	- : -	- 4											
5.Fu /hr) ( or die					100 miles 100 mi		30												2V.)							
sg) 3					÷.,,				۸										1777	**:	3.3		441			
웊			5, s.   		54						1 - 5 -			** -											4	
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)					No.												1.0	·								
4.Fuel Rale: n/stroke @ peak (for diesel only)	33.9	33.2	33.2	33.2		12					• 1					. 14 1		: 	7.7				13			
#.Fue troke or die		(,	Fig. 1								0.0							··								
, s/mr	12 12 17																									
_														٠.			34 33									
PM ss)	20	90	20	8	\$ 5 2.5	* .3.					1.						- 4								***	
3.BHP@RPM (SAE Gross)	08	42.7/3000	42.7/3000	/30	5.7									- 1			13.								- 15. - 15.	
BHF SAE	41.4	12.7	42.7	42.7	: \ :								Ches.	-		 									· J	
6, -	41.4/3000			3									New York												*	
<del>-</del>		4 1			18 g		3,4		3		C		1		(A)			- 31 5-31							1	
lode		N.	7	AG.									1.0	- 1			\$ 4. 1	N 1 1	3							
le N	1	4T-	41-1	1-1					100		1.1															
ngir	89	E8	8 <u>H</u>	8 E8			'n														100 Z					
2.Engine Model	3TNE84T-EDM	3TNE84T-EMP	3TNE84T-EYA	3TNE84T-EBM (32) 42.7/3000					133 A						10000											
								-	は、						が ない ない ない											
ode																										
Je C	A	Ą	A	K							(4.5) (4.5)		13		120									41.		
1.Engine Code	N/A	Ν	N/A	Y/N	13 13 13 13 13 13 13 13 13 13 13 13 13 1		PATE N		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		-1 14 -1 14			7 - 1 - 1 7 - 2 - 1 7 - 2 - 1 7 - 2 - 1			<b>大大</b>						1	-		
<u>1</u>									, å , , , , .																	
	-34.53	1	177	1		<u>L</u>		1	13:20	<u> </u>		<u> </u>	[	L	-3	1	100	1	KW11	1			1:25	1	153	<u>.                                    </u>