

YANMAR CO., LTD.

EXECUTIVE ORDER U-R-028-0125 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours) 5000						
2003	3YDXL2.00F4N	1.995	Diesel							
SPECIAL	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION							
	Direct Diesel Injec	tion	Generator Set							

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD				XHAUST (g/kw-ì	nr)		OPACITY (%)				
CLASS	CATEGORY		HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK		
19≤ kW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	N/A	N/A	N/A		
		CERT			8.9	5.1	0.50					

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Raphael Susnown

Executed at El Monte, California on this ______ day of December 2002.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Sr mary Form

Yanmar Co.,Ltd. Manufacturer: Nonroad CI Engine category:

EPA Engine Famiy: 3YDXL2.00F4N

Mfr Family Name: N/A

New Submission Process Code:

FO U-R-028.0125 ATTACHMENT

	1						13	は (数 海(数		in ick		्रेड	1	3	6								- A			
ol 930						:			,	3	1,3		Ç.	1				T			1:3					1
9.Emission Control Device Per SAE J1930	4	1	4.9	-	1	15			2,2	-	1.50 1.55	\rightarrow		3						-	12				2.3	
n C.	ΕM	5	ΕM	5	EM	EM DD	\ \frac{1}{2}	5		_	EW	_				á .			***	9			10		4.1	
ssio Jer	Ш	Ä	Π	EM		ĪŪ	EM	E	ЕM	EΥ	面	E	3						1		3.5		13			
Emi:	- Cal.				1								4.							-		Ž.	420			7
9.6 Jevi			6.10		- 47						.3				62											3
							3						*,													7
nb.c			\		2.2								7						2	1						
8.Fuel Rate: (lbs/hr)@peak torque	-	-	-	ا ہے [م ا	مدا	5	۔	305	بر [مدا	5		200											
of R	N A A	\X	N/A	¥ X	NA	X	N/A	Ϋ́	Ž	₹ Ž	N/A	Ϋ́					- (33)		12.5				*		1	
F. 6	1 40		27. 98.0						1000	-			13	1:							13					9
g yyh	1						14				10.		3] -]	4.3	,					1			1
=	- \$	-					**				1	30			7.3						7.5		13		12	
¥			12.5				1		15		3.7								23-19		200				2.0	
7.Fuel Rate: nım/stroke@peak torque			37.5				感		2		1.33		35]			200 a 7					-	\$1	3
uel Ra troke@ torque	NA	X X	N/A	N/A	N/A	Ϋ́	N/A	¥ X	Ş	N/A	N/A	Ϋ́	*		0 L 7								13			1
7.Fuel Rate: n/stroke@pe torque	1	-	.5	-	5.5	-	1	~	-	[-	Y.		3.5						100					
7. /mi							il.		×. *	-		-	198		3		-	1			Α,		5		1.32	- *
=	3				1163			1			1.0		<u></u>						7				1.5			
			15.5														1								3	
d ∵	1								***		200		*		re resi		**************************************			1	4	1	- 41		2	
6.Torqua @ RPM (SEA Gross)	A	A	4	4	N/A	4	4	_	-	٠,	-	-	1	1		2.							樓			
9 G	N/A	N/A	N/A	Y X	ž	ž	A/A	A/N	N/A	N A A	N/A	Ϋ́					3.44				1				1	
orq SE/														1			1		1.0						34.	
6.T)								1	\.						73.5					1	3				***	5
	<u> </u>																				1.9				-3	
= ~											19						13.5				10.3					-
5.Fuel Rate: (Ibs/hr) (@ peak HP (for diesels only)			5					-							1 T. C.				10		1		隧			-
5.Fuel Rate: /hr) (@ poak or diesels onl	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	9.7	7 20	1				1	ءِ ر		¥					
Fuel r) (c) Jies	6	6	6	G.	G.	G	6	6	6	6	0	6		İ	126.0				25.73						1	
5,J ts://w for c		Ì		. ,			. S.		<u>.</u>		÷.												1.04			
€~							1.37								120								2.5	- 11 p		
₾						١.		12.	27.92					1	1-3				5.0							
ate: peak FIP only)									9		3.47										143	- 77	72.5			
	IJ	5	5	5	ហ	5	2	2	5	5	വ	5			35											
4.Fuel R Nstroke (@ (for diesel	24,	24.	24.	24,5	24.5	24.5	24.5	24	24.5	24.5	24.5	24.										_	. 6			
골 동 후			. 52							`	(2)								1		1	T i j		Mil.	33	
4.Fuel R mm/stroke @ (for diesel	24,				47														77			. '	1.5			
Ē	2.7											-				-	3 1		17.5	÷ **	3	, i.e.	4.6	Ė.	ž.,	
			1		y Duci												,							<u>.</u>		
PM Ss)	00	90	၉	8	2	9	8	9	8	8	2	2									40°9 1885			٠.	-,-	
(()) Gro	18	<u>~</u>	8	38	18	18	18	18(18(186	18(186			7.1				υ.				31		30	
3.BHP@RPM (SAE Gross)	26.5/1800	26.5/1800	26.5/1800	26.5/1800	26.5/1800	26.5/1800	26,5/1800	26.5/1800	26.5/1800	26.5/1800	26.5/1800	26,5/1800	×	1				11:1					, X	[* #] .		
3.B	26	26	26	26	26	26	26	26	26	26	26	26					7.4		7						12	
				4,5			7.3				15						5		3.	. :		2.3			-2.5	
-				146												45	., .,		7 J				14213 1514	- 11	-9	
ode	Σ	9	4	4TNE84-EAD	13	14	ည	\geq	Y.	81	В.	5	4.0		5		7.5		iĝ.	7	-6.5					
ž		Ð	G	Ď,	EG	EG	<u>بر</u> الل	岩	щ	ΕĠ	G	ΕA	ન અંદિ -	1.7	13.1	14.					v. (4)					
ine	7	34-	4	84	34:	34-	<u>7</u>	7 −	78	<u>4</u>	7.	7		٠.	1					Ų.					ò	
ngi	Ä	逆	<u> </u>	뿐	ij.	ij	Щ	필.	Ż	ij	ΞŢ	Ę	<u></u>	1.	3.	11	(1,17) (1,17)		٠ د		3.7				1	
2.Engine Model	4TNE84-EDM3	4TNE84-EJG1	4TNE84-EG1A	4T	4TNE84-EG1A	4TNE84-EG1A	4TNE84-EYAG	4TNE84-EKRV	4TNE84-EK	4TNE84-EGB1	4TNE84-EGB1	4TNE84-EAD1		d.				15 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		:: 1						
• •	200	-			2	7	4	7		7	7	4	.5							4.					4	
Je			1.5			<u> -</u> -			4		注									is the					(A)	
Ö													,			:									Ž.	
) e (K.	⋖	¥.	⋖	₹	∢	4	N/A	N A	K	$\boldsymbol{\alpha}$	A	3	À						ář.						# (T
1.Engine Code	N/A	N/A	N/A	N/A	Α/N	Y/A	NA	Ž	Z	N/A	N/A	N/A		445						-			2		3	
пj				1						.4.70				•		: +			*					73	-2	3.4
←	÷.	<i>.</i> 2	:				- 3	e de	7-3-	<u>. h.</u> j			V	: .			<i>E</i> ,			_:_	3.7				7.4	-