California Environmental Protection Agency AIR RESOURCES BOARD	YANMAR DIESEL ENGINE CO., LTD.	EXECUTIVE ORDER U-R-028-0096 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2003	3YDXL1.33M3N	1.331	Diesel	5000

SPECIAL FEATURES & EMISSION CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION
Direct Diesel Injection	Crane, Loader, Tractor, Dozer, Pump, Compressor, Excavator

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19 ≤ KW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	20	15	50
		CERT	--	--	6.6	4.2	0.42	2	3	3

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 21ST day of March 2002.

Allen Lyons, Chief
New Vehicle/Engine Programs Branch

Engine Model Summary Form

Manufacturer: **Yanmar Diesel Engine Co.,Ltd.**

Engine category: **Nonroad CI**

EPA Engine Family: **3YDXL1.33M3N**

Mfr Family Name: **N/A**

Process Code: **New Submission**

ATTACHMENT

EO U-R-028-0096

Page 1 of 2

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
N/A	3TNV82A-VM2	31.0/3000	27.2	13.5	67.1/1000	30.5	5.0	DDI
N/A	3TNV82A-JMA	30.7/3000	26.9	13.3	64.9/1200	29.0	5.8	DDI
		23.1 kw						
		22.9 kw						

Engine Model Summary Form

ATTACHMENT

EO U-R-028-0096

Page 2 of 2

Manufacturer: **Yanmar Co.,Ltd.**

Engine category: **Nonroad CI**

EPA Engine Family: **3YDXL1.33M3N**

Mfr Family Name:

Process Code: **Running Change** Sep. 5, 2002

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
N/A	3TNV82A-D	30.6/3000	26.8	13.3	64.1/1200	28.4	5.6	EM DDI
N/A	3TNV82A-I	29.5/2900	26.5	12.7	64.1/1200	28.4	5.6	EM
N/A	3TNV82A-K	28.4/2800	26.1	12.1	64.1/1200	28.4	5.6	EM
N/A	3TNV82A-L	27.4/2700	25.8	11.5	64.7/1200	28.6	5.7	EM
N/A	3TNV82A-M	26.3/2600	25.4	10.9	62.7/1100	27.9	5.1	EM
N/A	3D82AE-5M	26.3/2600	25.4	10.9	62.7/1100	27.9	5.1	EM