YANMAR CO., LTD.

EXECUTIVE ORDER U-R-028-0098 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)					
2003	3YDXL2.09K4N	2.091	Diesel	5000					
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION						
*7	Direct Diesel Injec	etion	Compressor, Re	frigerator					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	C	OPACITY (%)					
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK	
19 ≤ KW < 37	Tier 1	STD	N/A	9.5	N/A	5.5	0.80	20	15	50	
		CERT		6.3		3.0	0.27	4	4	4	

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of October 2002.

Aller Lyons, Chief

Mobile Source Operations Division

Yanmar Co.,Ltd. Manufacturer:

Nonroad CI Engine category:

EPA Engine Family: 3YDXL2.09K4N

Mfr Family Name: N/A

**New Submission** Process Code:

EO No. U-R-028-0098 Pege 1 of 2

			•												•
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930			1							, 1750 3 750 3 750	, Asia		1.50		Ī
of Party	EM, DD1	EM DOF	EM DD[		1.7	15		- H	(nert)		Ġ.	8.0			
A S			<b>↓</b>												
sion er S										14.34		20,4			
niss P	V. (a.)											ųi	16.		1
<u>,</u> i.							×				.0.7		136		1
De C				1						1.4	1				
<b>e</b>						1 4 4				d-fig.		353			
<u></u>															-
Sat Fr		_	6			1324		. Jack .				11.04			
<u> </u>	8.9	8.9	8.9									44.			
<u> </u>									7.73						
8 4/s	1 2 2							1.00	13.15			9			
€											U. P.				
×						100	- 1				1.35	190			
e: pea			1					10.					10.00 10.00		1
Fag at		$\Xi$							133			70	la seri		
a ski	8	34.1	34.1						- 4						
7.Fuel Rate: mm/stroke@peak torque		1				044					3.3				
Ē				-	1					1.33		13.4		'	
						ĵ.							E A		
_	7.7.										(86.5		36.5		
6.Torque @ RPM (SEA Gross)	102.0/1200	102.0/1200	102.0/1200			ija.il					1 (1 (4 (4 (4 (4 (4 (4 (4 (4 (4 (4 (4 (4 (4	.61			1
@ 2	12	112	12						\$450 66	1.3	1 Tar				
A Ve	0	0.0	0							5 % A		2.			
S.E.	12	102	20												
6.T	`	ľ							17.2						İ
					1		1.50 T		(3,3	K.		3.11			
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)				40				1 2 2							
9 X E			A Son												į
Rad	-	Ψ.	-						1750			3.4		146	
<u> </u>	13.1	13.1	13.1		14 EX		77 - () 5 - ()					251			
5.F				aty.A					100						
(B)	10.0		¥131	7.45		483	34.4					100			1
_												41			ĺ
노		·							134 Y			3.1			
? 粪 돌				11.					4.3						
ਭਾਲ ਸ਼ੁਰੂ ਹੁਣ ਹੁ	27.2	27.2	27.2							70 (1.54 30 (1.54 - 61 (20)			1.0		
ese.	27	27	27										2.5		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)				4-11							1.58				
s s															
E					A. 6							5.4			
	46 61 m									* 1		7 10			1
3.BHP@RPM (SAE Gross)	33.9/2200	0	33.9/2200	25.3 km									\$ 3		1
2 S	$\tilde{z}$	33.9/2200	$\tilde{z}$	$\sim$		4.31							<b>15</b> 5		l
<del>Б</del> пі	6	6	6	-											I
S.B.	33	33.	33	2										1 ***	i
(7)	ti i i i Agiliy			$\circlearrowleft$											
							3.0					1 mg 4 6044			
<u> </u>	>						1.45	3.5		54,			4.3		
<u>0</u>	Ş		TK486VB												•
2	关	TK486V	20			200			94.0				0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
į.	98	4	48								3 3				
,ii	$\geq$	户	Ϋ́										7.3		
2.Engine Model	4TNV86TK-VM				27 to 5 to 1			1							
	1.3					1			1.6	1.07	5.				
<u>a</u>		Ì						3.7							-
ŏ															
) e	4	4	~		10 mg										
gin	N/A	Y Y	ΝΆ												
1.Engine Code		- 1													
<del>-</del>		ľ					為有	N.Y					Page 12		İ
	1														

## Engine Model S many Form

Yanmar Co.,Ltd. Manufacturer:

Nonroad Cl Engine category:

EPA Engine Family: 3YDXL2.09K4N

Mfr Family Name:

Running Change Process Code:

ATTACHMENT 2 OFZ

U-R-028-00g

		•			1,20		·				*		anjyar Far	- 3 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2					1,000s		400	1 44	100	
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930										1.		1 1				. [						. }		
草子																							ng).	
ડ મું	_			6. : GHZ														ļ						
sior er S	Ξ			14.00 17.00 18.00																				
e Tiši														.										
Ž. Š.		3								1	1. (4)			].									11.0	-
۵ ۵				93					1.4							·								1
ė								3.5					294											
		2.4	-				i .				1,125													
Rate ak t	m			400 g	] - [										Ä									
e g	9.3	l 2.			1			8							17		1							
8.Fuel Rate: hr)@peak to																								ĺ
8 s/h				e eri erioe	1					)			12.1											
€				7.7.				1 14							. 14			l	1 1 12 15					ĺ
v						1 1 1					3.0												100	
ea.								34			100										100			
e @ gate	-			1 <sub>00,1</sub>							3.7													
uel Rat troke@ torque	27.1																k j		.: ::					İ
.F./stn /stn		1.2													- 6. - 1									
7.Fuel Rate: mm/stroke@peak torque																			100					
_	and a	E, i		d														ĺ	43 °.					
	-										1 de 23		di.	1										
6.Torque @ RPM (SEA Gross)	87.4/1560	Ľ.	1						\$ 99															
SSS SSS	99		]					100					et ei				.3						teo ik	
9 Q	7			ciyyi Tiy										1	ja j		1.54 TA		1998 P					
턀낁	×				-																			
5.00	Ι Ψ	1983						4 - 7			100													
· ·					ŀ	1 1 1 1 1					1 1 1				y y h Mirae						1000		100	
	CST.																							
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)					1										ă.		C4							
5.Fuel Rate: lbs/hr) @ peak Hi (for diesels only)	m			Ĕ.																			(44)63 (32)	
조(년) 8 8년 전 기원	13.8				<b>.</b>																 			
F. (F. ep.			1								102													
5 Js/ł for					1	7-4							1		- 40				3.				K#II	
€ *					1										독일									
<u>c</u>			, ,	Jana'		44							1.5					1						
ate: peak HP only)								3K (1		11											N.		1,	
ate pe	0														(1)									
<u>교</u> @ 호	4	2 12 2 97.			1		1	100																
P. Se e	24.0				İ				1 1				1.										3 <b>3</b> 4	
4.Fuel Rate: mm/stroke @ peak F (for diesel only)																								
Ë		M.		, s. i									ell Velksig		1 8/ 58%									
_																								
₹ ~								3 1	1 44		1973	İ												
RPI oss	S.			4		٠ <u>.</u> .						٠.									lari,			
இந்	12	ľ		-	1	Latin					1. 2.			{										
3.BHP@RPM (SAE Gross)	35.0/2600																							
3.6	<b>ന്</b>	•			1					4			F											
		l		- 14 h		4.													100				1. 12	1
_										.   .														
ģ	-							١						Ì										1
Š	I																							
2.Engine Model	TK486VH							100																
iĝ	4						-				10.75						"							
ᄪ	F										-:													
7	.		]				ĺ				1				* *									1
•		į.		*1			1	1.					ş÷				America America							
ğ				Ç.		1								1			Agr.		32° 5					
ပိ								1 : :					h				1.5							
<u>ā</u>	N/A			46						1			4 <sup>3</sup> -											
īġ.	Ż			1 475				1 3 V							الرج		-21							
1.Engine Code													ber i			-								
<del>-</del>				1 4							. 476													ĺ
	لـــــــــــــــــــــــــــــــــــــ	 للت	<u> </u>		l		i	<u> </u>	<u> </u>	<u>.:!</u>		l		LL	لقت			l	L	l	لتقدنا			L