Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR) ENGIND CARNEY DISPLACEMENT		FUEL TYPE	USEFUL LIFE (hours)		
2003	3MVXL01.3AAA	1.1, 1.3, 1.5	Diesel	3000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Indirect Diesel Injection			Tractor, Generator and Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
8 <u><</u> KW < 19	Tier 1	STD	N/A	N/A	9.5	6.6	0.80	20	15	50
		CERT			5.4	0.8	0.22	3	3	50

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 2774 day of January 2003.

Allen Lyons, Chief

Mobile Source Operations Division

ATTACHMENT 1 OF 1

Engine Model Strang Form

Manufacturer: Mitsubishi Heavy Industries,Ltd

Engine category: Nonroad Cl

EPA Engine Family. 3MVXL01.3AAA

Mfr Family Name: S3L2

Process Code: New Submission

U-R-035-0038

1.Engine Code 2.Engine Model (SAE Cross) S3L2-W263ES S3L2 24.4@2400 S3L2-W261DG S3L2 18.9@1800 S3L2-W261W S3L2 18.9@1800 S3L2-W261W S3L2 18.9@1800 S3L2-W261W S3L2 18.9@1800 S3L-W214RH S3L 20.3@2500 S3L-W261DG S3L 31 20.3@2500 S3L-W261DG S3L 32 15.2@1800 S3L-W261DG S3L 32 21.5@1800 S3L-W261DG S3L 32 21.5@1800 S3L-W261DG S3L 32 21.5@1800 S3L-W261DG S3L 32 21.5@1800 S3L-W261DG S3L 21.5@1800 S3L-W215RH S3L 21.5@1800 S3L-W215RH S3L 21.5@1800 S3L-W215RH S3L 21.4@28000 S3L-W215RH S3L 24.4@28000 S3L-W215RH S3L 24.4@28000
A Fool Rate: A mm/stroke (et peak) (for dieset only) 27.7 27.1 27.1 27.1 27.1 22.1 22.4 22.4 22.3 22.3 22.3 22.3
5.5 tool (tade: 111) ((to: (the:/in))
6. Lonquic @ HPM (131 A Chorse) 59.3 @ 1800 58.6 @ 1800 59.3 @ 1350 59.3 @ 1350 59.3 @ 1350 47.7 @ 1600 47.7 @ 1350 47.7 @ 1350 47.7 @ 1350 47.7 @ 1350 52.2 @ 1350 47.7 @ 1600 47.7 @ 1600 58.6 @ 1800 58.6 @ 1800
7.Fire! Hale mm/stroke@peak torque 28.8 28.8 27.5 27.5 27.5 27.5 22.5 22.4 22.4 22.4 22.4 23.2 23.2 23.2 23.2
8 Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J 1930 8.5 (DI
9.Emission Control Device Per SAE J 1930 IDI IDI IDI IDI IDI IDI IDI IDI IDI ID