## ISEKI MATSUYAMA MFG. CO., LTD.

EXECUTIVE ORDER U-R-038-0010 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2003	3ICLL0.93B3C	0.929	Diesel				
	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION				
	Indirect Diesel Inje	ection	Tractor				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION		EXHAUST (g/kw-hr) OPACITY (%)							
	STANDARD CATEGORY		нс	NOx	NMHC+NOx	co	РМ	ACCEL	LUG	PEAK
8 <u>&lt;</u> KW<19	Tier 1	STD	N/A	N/A	9.5	6.6	0.80	20	15	50
		CERT			7.3	2.3	0.53	7	7	8

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of January 2003.

Allen Lyons, Chief

Mobile Source Operations Division

## ATTACHMENT 1 OF 1

Engine Model St. mary Form

U-R-038-0010

Manufacturer: ISEKI MATSUYAMA MFG. CO., LTD.

Engine category: Nonroad Cl

EPA Engine Family. 3ICLL0.93B3C

Mfr Family Name: NONE

Process Code: New Sub - continued

	<b>1</b>						LOWELL S			ATT 6	
ol 930										11.2	
Sontr E J1		1.3									
ion (	正										
miss e Pe											
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930											
ne C											
te: torq	3.2					_					
ll Ra oeak	@ 40	ŀ									
.Fue	6.0@40.2										
8 lbs/h											
te: peal	0.2										
7.Fuel Rate: mm/stroke@peak torque	19.9@40.2										
Fue stro tor	19.9				-						
7 mm			174								
						200	1.7				
S)	8										
6.Torque @ RPM (SEA Gross)	40.2@1800										
rque EA (	3.2										
6.To (S	4				Manager and control						
. 분 좋	က					::					
Rate peak ils or	16,							,			
ruel () ()	7.5@16.6					. + 0.			7.7		
5.Fuel Rate: (bs/hr) @ peak HP (for diesels only)	7										
€ -							1. F				-
天 元	9										
kate: pea only	17.8@16.6										
uel F ke @ liese	.8@										
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	17										:
E .											
3.BHP@RPM (SAE Gross)	16.6@2500										
@ ©.⊊	(05										
3.BH (SAI	16.6					-					
		-									_
<u> </u>				1							
<b>J</b> od											
<u></u>	E393	ŀ	-								
ngi	Ш		-	1 1							
2.Engine Model											
										-	
;ode											
Je C	¥										
1.Engine Code	N/A					-					
<u>т.</u>											
										 ii	