California Environmental Protection Agency

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4CEXL015.AAD	15.0	Diesel	8000		
SPECIAL	FEATURES & EMISSION		TYPICAL EQUIPMENT	APPLICATION		
Direct Dies	el Injection, Turbocharge Powertrain Control M	er, Charge Air Cooler, Module	Loader, Tractor and Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD				EXHAUST (g/kw-ł	<b>нг)</b>		0	PACITY (%	6)
CLASS	CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
225 <u>≤</u> kW < 450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	20	15	50
		FEL	N/A	N/A	5.6	N/A	N/A	N/A	N/A	N/A
		CERT			5.5	0.6	0.13	12	2	38

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

## This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-R-002-0219-2 dated February 17, 2004.

Executed at El Monte, California on this

\_\_\_\_ day of September 2004.

Allen I

Allen Lons, Chief Mobile Source Operations Division

Engine Model Summary Form Arraduleor Pg (af 1

W-R-002-0219-3

Manufacturer:Cummins Inc.Engine category:Nonroad CIEPA Engine Famity:4CEXL015.AADMir Family Name:F103Process Code::New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diese! only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mrr/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930
8489:FR10317	QSX15-C	360@2100	186	131.7	1215@1400	244	115.4 01	15.4 DUT PCM,TC,CAC
8489.FR10345	QSX15-C	380@2100	193	136.7	1161@1400	233	109.8	PCM,TC,CAC
8489:FR10372	QSX15-C	375@2000	194	130.8	1380@1400	1 280	132.4	PCM,TC,CAC
8489:FR10380	QSX15-C	350@2100	180	127.7	1180@1400	239	112.7	PCM,TC,CAC
8489:FR10385	QSX15-C	360@1800	172	121,8	1230@1400	243	114.8	PCM, TC, CAC
8571:FR10317	QSX15-C	360@2100	186	131.7	1215@1400	244	115.4	PCM, TC, CAC
8571:FR10345	QSX15-C	380@2100	193	136.7	1161@1400	233	109.8	PCM.TC.CAC
8571.FR10372	QSX15-C	375@2000	194	130.8	1380@1400	280	132.4	PCM,TC,CAC
8571:FR10380	QSX15-C	350@2100	180	127.7	1180@1400	239	112.7	PCM,TC,CAC
8571:FR10385	QSX15-C	360@1800	172	121.8	1230@1400	243	114.8 0	PCM.TC.CAC