Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4CEXL0239AAD	3.9	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger, Charge Air Cooler			Crane, Loader, Tractor, Pump and Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams-per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)			OPACITY (%)				
CLASS			нс	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
75 <u>≤</u> kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		FEL	N/A	N/A	6.2	N/A	N/A	N/A	N/A	N/A
		CERT			5.3	0.6	0.18	12	3	35

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-R-002-0229 dated September 11, 2003.

Executed at El Monte, California on this \_\_\_\_\_ day of February 2004.

Allen Lyons, Chief Mobile Source Operations Division

ومراجع المراجع والمستور فيتعلق والمسترين والمستري والمستري والمستري والمستري والمستري والمستري والمستري والمستر

Engine Model S mmary Form

·.

ATTH. HMENT 1 OF 1 Cummins Inc. Manufacturer:

Nonroad Over 50 HP Engine category:

4CEXL0239AAD EPA Engine Famly.

1-9250-202-D-A-U

Mir Family Name: C383 Process Code:

**New Submission** 

	4						
ol 930		1.					
i Jt	,AC	AC	AC	AC			
on C SA	ы С	0	00	0			
nissi Per	DDI,TC,CAC	DDI,TC,CAG		DDI,TC,(			
9.Emission Control Device Per SAE J1930	D	DĽ	0[	Da			
_							
. bu		ļ					
8.Fuel Rate: hr)@peak tor	0	4	3	2			
uel F ppea	33.0	36.4	31.3	31			
8.Fuel Rate: lbs/hr)@peak torque			-				
sdl)	24						
¥				- (N			
7.Fuel Rate: nm/stroke@peak forque			5.0				
7.Fuel Rate: Vstroke@pe torque	[13	108	107	93			
Stro for	40	Ľ	Ľ.				
7		ŀ.					
×	0	0	0	0			
(sso	130	50	130	150			
.Torque @ RPM (SEA Gross)	355@1300	345@1500	155@1300	330@1500			
lorq (SE	35	345	35	33(			
 0	200						
<u>م</u>							
e: htH							
Rat pea els o	48,2	1,4	5.	3.4			
5.Fuel Rate: lbs/hr) @ peak HP (for diesels only)	46	44	41	40			
5.1 bs/h (for i							
$\sim$							
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)				0.0			
ate: peak f only)							
4.Fuel Rate Vstroke @ pe (for diesel on	67	79	84	88			
a.Fu troke ar di				, in			
, ltc (tc ,							
E							
Χœ	0	0	0	o l			
APP Fross	220	250	220	520			
).BHP@APM (SAE Gross)	125@2200	0	0	6			
3.B (S/	12	11	110@2200	11			
<u></u>	:- ·			0.46			
pot	AA	B3,9-VE-TAA	AA.	AA.			
e V		L.	E-1	Ш			
ŋ	9-V	9 <del>.</del> V	9 <b>-</b> V	2 			
2.Engine Model	B3,9-VE-TAA	B3,	B3,9-VE-TAA	B			
de	43	64	95	81			
ပိ	311	3110	311	307			
jine	ERG	FRE	FR	FR			
L.Engine Code	1039;FH91143	238;FH91164	1239;FR91165	943;FR90781			
	80	82	82	29			
-							