Cummins Inc.

EXECUTIVE ORDER U-R-002-0236-3 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)	
2004	4CEXL0359AAD	5.9	Diesel	8000	
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION		
Direct Diesel Injection, Turbocharger, Engine Control Module			Loader, Tractor, Dozer, Pump, Compressor		

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER		EXHAUST (g/kw-hr)					OPACITY (%)			
CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
75 ≤ kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		FEL	N/A	N/A	6.4	N/A	N/A	N/A	N/A	N/A
		CERT			6.0	1.2	0.25	9	4	17

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-R-002-0236-2 dated June 14, 2004.

Executed at El Monte, California on this

day of September 2004.

Allen Jons, Chief

Mobile Source Operations Division

Engine Model Sur nary Form

Cummins Inc. Manufacturer:

Nonroad Over 50 HP 4CEXL0359AAD Englne category;

EPA Engine Famiy.

Mfr Family Name: C402

New Submission Process Code:

11-R-c02-0236-1

		34000	
0	34- xC		
8.Fuel Rate: 9.Emission Control [bs/ht/@peak torque Dovica Per \$AE J1930			
9.Emisslon Control ovica Per SAE J193	**(P)*///TOH;CM	. O	0.600
를 <u>하</u>		<u> </u>	
niss s Pe			
D.E.	<u></u>	26	
~ č	É-	-	
or it	3-2		
:e	124	- Wist	
enk enk	20 0	. .	38.9 38.8 1.31
8.Fuel Nate: hr)@peak tor			
1.0 kg			
Ë	2 7		
J			
3: Se 23	5.0		
9 E	(U) (D)	Ē	Nation ¹
7.Fuel Rate: mnVstroko@peak torque	1.92 199	9	177 1822 183 183
F. F.	200	†⊒2*, ! -[~].:	
Ë	9- <u>-</u>	<u> </u>	75.00
	7. T		
≥			
6.Torqua @ NPM (SEA Gross)	440@1500P	132@1500	973@1500 100@1700 140@1500
@ <u>Ş</u>		<u>~</u>	
grigo 		2	
<u> </u>	<u> </u>	3	;ē ₹ ÷ ÷
9			
_			
≒≩		k Ż	
eak cak		G	N-io G
5.Fuel Rate: lbs/hu) @ peak HP (tor diesels only)	<u> </u>	်က္က	*
	estorio: 2	1000	Fig. 1774
5 [bs/] (for	94.2		
=	3.1		
르			
当業会	21.15	J.,	
E E E	-c c	ي ت	(a (
uell ra (6 lies		1	
4.Fuel Rate: Vstroke @ peak (for diesel only)	30		
4.Fuel Rate: mm/stroke @ peak (for diesel only)	197.	1-07	
Ξ			
_			190@2500 190@2200 195@2300
, a.biip@ripm (sae Gioss)	155@2500 155@2200	140@2200	130@2500 135@2200 155@2300
9	, C	5	<u> </u>
AE AE			
. E	<u> </u>	Œ	
	# <mark>\QSB5,9-40-1</mark> \ \ \ \ \ \ \ \ \ \ \ \ \	0.0866,9-90-IF	
		1 2 2 1 2 2	
g	FIF	<u> </u>	
Ž	CSD5.9-80-II	8	QS86.9-30.T CQ\$66.9-30.T Q\$65.9-30.T
5	တ်င		C-C.C.
. <u>Ş</u>		Ü	高麗華
<u>.</u>		ď	já á á á
44			Control of the Contro
<u> </u>	(in) (c)		THE RESERVE AND ADDRESS OF THE PARTY OF THE
ζoς		2	
) 0	ic c	<u>-</u>	
1.Engine Code 2.Engine Model	1187,6501155 300 1891 156	Talligh Joseph	340;FR91159 341;FR91159 420;FR91255
Ę	18. 10.00	300	
_	<u> </u>		8 6 8