

Cummins Inc.

EXECUTIVE ORDER U-R-002-0236 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4CEXL0359AAD	5.9	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct D	iesel Injection, Turbocha Module	rger, Engine Control	Loader, Tractor, Dozer, Pump, Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)			OPACITY (%)				
POWER CLASS		:	нс	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
75 < kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		FEL	N/A	N/A	6.4	N/A	N/A	N/A	N/A	N/A
		CERT			6.0	1.2	0.25	9	4	17

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of November 2003.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Summary Form

Cummins Inc. Manufacturer:

Nonroad Over 50 HP 4CEXL0359AAD Engine category:

U-R-002-0236

EPA Engine Family.

Mfr Family Name: C402

New Submission Process Code:

30_	
9.Emission Control Device Per SAE J1930 RP TOLECAL TOLECAL TOLECAL TOLECAL	
ssion Con Per SAE. C.E.C. C.E.C.	0.0
ssion Co Per SAE C E C C C E C	шш
Issa Pe TC	E E
ice ive	
6 Q	
er	
8.Fuel Rate: (lbs/hr)@peak torque (1.5.46,55.4.45,1.5.7.7.7.44,4.4.7.7.7.7.7.44,4.4.7.7.7.7.7	
8.Fuel Rate: hr/@peak tor 46.5 7.45,1 38.9	∞ - '
el Rate peak 1 46,5 45,1 44,4 38.9	38.8 45.1
J. (0)	
8 ∰.	
×	
7.Fuel Rate: mr/stroke@peak torque torque torgue to	
ke@pke@pke@pke@pke@pke@pke@pke@pke@pke@p	ΩΩ.
uel Ra Iroke@ Iorque 92 89 89	
Vstu t	
.Torque @ RPM (SEA Gross) 440@1500 432@1500 873@1500	400@1400 440@1500
Torque @ RPI (SEA Gross) 440@150(432@150(373@150(<u> </u>
), (a . (a);
ord SE/ 14(10.4
6.7	
	and the
5.Fuel Rate: bs/hr) @ peak HP (for diesels only) 64,1 59.0 71 65,9	
1 2 6 5 5 5 6 5 5 6 5 6 5 6 5 6 5 6 5 6 5	တြင
5.Fuel Rate: s/hr) @ peak or diesels onl 64.1. 59.0 53.0	51.6 59.9
正色章 一	
S (lo l)	
H H	
:4 2 kg	
(Bate of Person	o aline
4.Fuel Rate: mn/stroke @ peak HP (for diesel only) 7.6 80 64	
正名 p	
L Salah	100
	- 5.0
≱	222
7. ros 22 (20)	
3.BHP@RPM (SAE Gross) 155@2500 155@2200 140@2200	150@2200 155@2300
SAI	8 8 8
6	
-	
多原压模 员	
Σ စြုစုစြ	7 (D) (7)
2.Engine Model	USBS9:30:11 USBS9:30:11 USBS:9:30-1
ig in	o o o
	j d á
ğ bi bi	1159 1255 1255
o EEE	5 5 5
	9,FF9 9,FF9
1.Engine Code 8187/HR911.55 8300/FR911.56 8939/FR911.57	÷ (ω)
<u>п</u> . 65 68 84	प्राप्त ज