



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2004	4JDXL02:9018	2.9	Diesel	8000
<b>SPECIAL FEATURES &amp; EMISSION CONTROL SYSTEMS</b>			<b>TYPICAL EQUIPMENT APPLICATION</b>	
Direct Diesel Injection, Turbocharger, Smoke Puff Limiter			Tractor, Pump, Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		FEL	-	-	8.8	-	0.43	-	-	-
		CERT	-	-	7.9	1.2	0.39	11	4	26

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 23<sup>RD</sup> day of December 2003.

Allen Lyons, Chief  
Mobile Source Operations Division

# Engine Model Summary Form

Manufacturer: **Deere Power Systems Group of Deere and**  
 Engine category: **Nonroad CI**  
 EPA Engine Family: **4JDXL02.9018**  
 Mfr Family Name: **320TA**  
 Class Code: **New Submission**

*Attachment 1 of 2*

*U-P-004-015*

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
3029TLV52	3029T	64.37@2400	64.00@2400	24.26@2400	176.26@1500	74@1500	18.30@1500	EM 007, J1930 TC

# Engine Model Summary Form

Manufacturer: **Deere Power Systems Group of Deere and**  
 Engine category: **Nonroad CI**  
 EPA Engine Family: **4JDXL02.9018**  
 Mfr Family Name: **320TA**  
 Process Code: **Running Change**

*Attachment 2 of 2*  
*U-R-004-0165*

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
✓ 3029TPY11	3029T	64.37@2400	64.00@2400	24.26@2400	176.26@1500	74@1500	18.30@1500	EM SPL <del>DOT</del> , TC
✓ 3029TLV52	3029T	64.37@2400	64.00@2400	24.26@2400	176.26@1500	74@1500	18.30@1500	EM SPL 0
✓ 3029TAT50	3029T	71.08@2300	71.70@2300	26.46@2300	195.43@1500	88.2@1500	20.29@1500	EM 0 ↓