Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL ENGINE FAMILY		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4JDXL06.8044	4.5, 6.8	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Dies Module	el Injection, Turbocharg e, Charge Air Cooler, Sr	er, Electronic Control noke Puff Limiter	Compressor, Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER	EMISSION STANDARD		EXHAUST (g/kW-hr)					OPACITY (%)		
CLASS	CATEGORY		нс	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
75 <u><</u> kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
		FEL	-	-	5.3	-	0.25	-	-	-
		CERT	-	-	5.2	1.0	0.23	9	3	22

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.


Executed at El Monte, California on this 23PD day of December 2003.

Allen Lyons, Chief Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: Deere Power Systems Group of Deere & Engine category: Nonroad Cl EPA Engine Family: 4JDXL06.8044 fr Family Name: 350HF New Submission . :ocess Code:

,



•

	2.Engine Model	· · · · · · · · · · · · · · · · · · ·	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930	SPL
6068HDW56	6068H JI 4	152.88@2200	76.20@2200	56.62@2200	496.32@1600	97.5@1600	52,78@1600	EM EC, 0 °F , 1	R, CAR
1999 - Bertefer Brazin, St. Landaum			۲۰۰۰ ۲۰۰۰ ۲۰۰۰ ۲۰۰۰ ۲۰۰۰ ۲۰۰۰ ۲۰۰۰ ۲۰۰		•		-		

Engine Model Summary Form

Attachment 2 0/2 U. R. 2014-0173

.

Ianufacturer:Deere Power Systems Group of Deere &Ingine category:Nonroad CIPA Engine Family4JDXL06.8044Mark350HFIs Code:Running Change

		3.0/11 0/11	ninvaroko o p+=	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
t.Engine Code	2.Engine Model 6068H	(SAE Gross)	(for diesel only) 75.60@2200	56.00@2200		96.4@1600	52.03@1600	DDT., TC, ECM- SPL, CAC