

## INTERNATIONAL TRUCK AND ENGINE CORPORATION

EXECUTIVE ORDER U-R-012-0062

New Off-Road
Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4NVXL0530ANE	8.7	Diesel	8000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Direct Dies	el Injection, Turbocharge and Engine Control N	er, Charge Air Cooler Module	Loader, Dozer and	d Tractor		

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS			HC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
130 <u>&lt;</u> KW<225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20		
225 <u>&lt;</u> KW<450	Tier 2	STD	N/A	N/A	6.4	3.5		<del></del>	15	50
_		CERT					0.20	20	15	50
	<del></del>				5.5	2.2	0.17	· 13	2	14

**BE IT FURTHER RESOLVED**: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of January 2004

Allen Lyons, Chief

Mobile Source Operations Division

## ATTACHMENT 1 OF 1

Engine Model Sur ary Form

•

Manufacturer: International E. O. # U-R-12-62

Engine category: Nonroad CI

EPA Engine Family. 4NVXL0530ANE

Mfr Family Name: DTA 530E

Process Code: New Submission

W-R-012-0062

	.4			e session	. 3 TS 2011 - 14			m 5 /	<u> </u>
8.Fuel Rate: 9.Emission Control (tbs/hr)@peak torque Device Per SAE J1930		93.7 DUI ECM,TC, CAC,	ECM, TC, CAC.	ECM,TC, CAC,	ECM, TC, CAC.	ECM,TC, CAC,	ECM,TC,CAC,	V ECM,TC,CAC,	4 10 11 20 11
8.Fuel Rate: (lbs/hr)@peak torqu	Average	93.7 D	89.6	114.1	89.2	82.3	73.8	92.9	The second secon
7.Fuel Rate: mm/stroke@peak torque	Average	215.2	205,7	200.4	204.8	189.0	169.4	163.2	
6.Torque @ RPM (SEA Gross)	Advertised	1075 @ 1300	1050 @ 1300	978 @ 1700	1050 @ 1300	950 @ 1300	850 @ 1300	822 @ 1700	with the state of
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	Average	120.3	127.3	123.3	113.2	117.2	98.2	102.4	The state of the s
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	Average	163.2	190.0	167.3	169,0	175.0	133,2	139.0	
3.BHP@RPM (SAE Gross)	Advertised	300 @ 2200	330 @ 2000	315@2200	300 @ 2000	300 @ 2000	265 @ 2200	265 @ 2200	1.262
2.Engine Model		ICH300D	C330D	IC315D	ः ।C300D	ICL300D		ICL265D2	
1.Engine Code		ICH300D	10330D	IC315D	{-€/-(C300D	ICL300D	ICH265D2	ICL265D2	Additional control of the control of