Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEARENGINE FAMILY20044NVXL0530ANF		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours) 8000			
		8.7	Diesel				
SPECIAL	FEATURES & EMISSION		TYPICAL EQUIPMENT APPLICATION				
Direct Dies	el Injection, Turbocharg and Engine Control I	er, Charge Air Cooler Nodule	Generator				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD				EXHAUST (g/kw-l	OPACITY (%)				
CLASS	CATEGORY		HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
130 <u><</u> KW<225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	N/A	N/A	
225 <u><</u> KW<450	Tier 2	STD	N/A	N/A	6.4	3.5	0.20	N/A		N/A
		CERT			5.3	2.0	0.14		N/A	<u>N/A</u>

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

___ day of January 2004.

Aller Lyons, Chief Mobile Source Operations Division

and the second second

ATTACHMENT 1 OF 1

Engine Model Sur any Form

·

 $\left(\begin{array}{c} \end{array} \right)$

.

Manufacturer: International E. O. # U-R-12-63

Engine category: Nonroad Cl

EPA Engine Family: 4NVXL0530ANF

Mfr Family Name: DTA 530E Process Code: New Submission

0

		3						- -		Şiş.		10 1-	Line of the second s	2
9.Emission Control Device Per SAE J1930		DDT ECM. TC. CAC.	ECM. TC: CAC:	ECM. TC. CAC.	ECM. TC. CAC.	ECM. TC. CAC.	ECM. TC. CAC	ECM. TC. CAC.	生きななどを			1 Mar Section Processing States		Contract to contract of the second second
	開三邊	ECN	ECN	Ц С С	ECV	ECN	ECV	ECN				80.9 20		
te: torque	ୁ ୁ							>				11. 1		
8.Fuel Rate: lbs/hr)@peak torque	Average	A	NA	AN	NA	AN	NA	A						
8. (Ibs/hr						- 			19. J. S.					
ate: Dpeak	e0									2010 1011 1011				
7.Fuel Rate: mm/stroke@peak torque	Average	AN	NA	¥	NA	AN	AN.	AA	4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
L MM			े र र स											
) RPM oss)	ised													
6.Torque @ RPM (SEA Gross)	Advertised	AN	NA	AN	ΥN	AN	AN	AN						
5.Fuel Rate: (bs/hr) @ peak HP (for diesels only)	age	2	0	e.	9	-	2							
5.Fuel Rate: bs/hr) @ peak HI (for diesels only)	Average	125.2	123.0	133.3	121.6	124.1	118.2	115.1						
sqi) dH	1 y 1													
	age	2	1	-	0	æ	2	-						
4.Fuet Rate: mm/stroke @ peak (for diesel only)	Average	249.2	204.1	221.1	242.0	205.8	235.2	229.1						
s/uu t)														
gRPM ross)	ised	1500	1800	1800	1500	1800	1500	1500	either	25 or	000)5 or	275	
3.BHP@RPM (SAE Gross)	Advertised	330 @ 1500	350 @ 1800	325 @ 1800	310 @ 1500	305 @ 1800	300 @ 1500	275 @ 1500	can be either	GCA325 or	GCB300	GCA305 or	GCB275	
~		-							C	_				
e Modé		330	350	325	310	305	GCB300 1	275		325		305		
2.Engine Model		GCB330	CCA350	GCA325	GCB310	GCA305	GCB	GCB275		GCD325		GCD305		
	0.00									-				
ie Cod		1330	350	325	310	305	300	275	atings	325	1.1	305		
1.Engine Code		GCB330	4 GCA350	GCA325	© GCB310	GCA305	GCB300	GCB275	Dual ratings	GCD325		GCD305		
-	369 2.3		اليانية من اليوسي من											_

U-R-012-0063