California Environmental Protection Agency AIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2004	4KBXL02.0FAD	1.999	Diesel	8000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT A	APPLICATION		
In	direct Diesel Injection, T Smoke Puff Limiter (Son	urbocharger, ne Models)	Compressor, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD			E	EXHAUST (g/kw-l	hr)		0	PACITY (%	()
CLASS	CATEGORY		нс	NOx	NMHC+Nox	со	РМ	ACCEL	LUG	PEAK
37 <u>≤</u> kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		CERT			5.9	0.9	0.25	8	5	24

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of August 2003.

Allen Loons, Chief Mobile Source Operations Division

Engine Model Sr mary Form

Attachment pg 1 of 1

Manufacturer: KUBOTA Corporation Engine category: Nonroad CI EPA Engine Family. 4KBXL02.0FAD Mfr Family Name: N/A

New Submission

Process Code:

. --

. 1

N-R-025-0142

**

V2003-HT-ES 59.0@2800 38.7 24.2 121.8@1600 42.0 15.0 V2003-HT-ES 59.0@2800 38.7 24.2 121.8@1600 42.0 15.0 V2003-HT-ES 59.0@2800 38.7 24.2 121.8@1600 42.0 15.0 V2003-FES 59.1@22600 38.7 24.2 116.2@2200 42.0 15.0 V2003-TES 55.1@22600 38.7 24.2 116.2@2200 38.7 10.0 V2003-TES 55.3@2600 39.1 22.7 120.7@1800 41.0 16.5 V2003-TES 55.3@2600 39.1 22.7 120.7@1800 41.0 16.5		2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for dieset only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr) @peak torque	9. Emission Control Device Per SAE J1930	
V2003-HT-ES 55.0@2800 38.7 24.2 12.18@1600 42.0 15.0 SPL V2003-TES 55.0@2800 38.7 24.2 12.18@1600 42.0 15.0 WH V2003-TES 55.0@2800 38.7 24.2 12.18@1600 42.0 15.0 WH V2003-TES 55.0@2800 38.7 24.2 116.2@2200 38.7 19.0 WA V2003-TES 55.9@2600 39.1 22.7 120.7@1800 41.0 16.5 WH V2003-TES 55.9@2600 39.1 22.7 120.7@1800 41.0 16.5 WH	X V2003-M-T-ES01	V2003-M-T-ES	59.0@2800	38.7	24.2	121.8@1600	42.0	15.0	NIA INT	ŧ
V2003-TES 55.0@2800 38.7 24.2 121.8@1600 42.0 15.0 144 V2003-TES 55.9@2800 38.7 22.5 121.8@1600 42.0 16.9 144 V2003-TES 55.9@2800 39.1 22.7 120.7@1600 41.0 16.5 144 V2003-TES 55.9@2800 39.1 22.7 120.7@1600 41.0 16.5 145 V2003-TES 55.9@2800 39.1 22.7 120.7@1600 41.0 16.5 145 V2003-TES 55.9@2800 39.1 22.7 120.7@1600 41.0 16.5 145	-ES01b	V2003-M-T-ES	59.0@2800	38.7	24.2	121.8@1600	42.0	15.0	† 	<u>,</u>
V2003-TES 54.8@2600 38.7 22.5 121.8@1800 42.0 16.9 WM V2003-TES 55.9@2600 38.7 24.2 116.2@2200 38.7 13.0 WM V2003-TES 55.9@2600 39.1 22.7 120.7@1800 41.0 16.5 WM V2003-TES 55.9@2600 39.1 22.7 120.7@1800 41.0 16.5 WM	ES01	V2003-T-ES	59.0@2800	38.7	24.2	121.8@1600	42.0	15.0	¥/A	
V2003TES 55.9@2600 38.7 24.2 116.2@2200 38.7 19.0 WM V2003TES 55.9@2600 39.1 22.7 120.7@1600 41.0 16.5 MM	ES02	V2003-T-ES	54.8@2600	38.7	22.5	121.8@1800	42.0	16.9	* #	
V2003-TES 559@2600 39.1 2.27 120.7@1800 41.0 16.5 WM	ES03	V2003-T-ES	59.0@2800	38.7	24.2	116.2@2200	38.7	19.0	W/W	
	ES04	V2003-T-ES	55.9@2600	39.1	22.7	120.7@1800	41.0	16.5	N#W	
		AND A COMPANY PRACTIC CONSISTENCE OF A			: : :					
						· · · · · · · · · · · · · · · · · · ·				
					-					
				-						
				a start of a start of						
		· · • • • • • • • • • • • • • • • • • •								
					-					
									-	

				-		And the second second second second				
			•		•	•				
					······································			· · · · · · · · · · · · · · · · · · ·		
								Les Merils Strategies		
		•						and the second of the second		15.00
				-						e4
