EXECUTIVE ORDER U-R-035-0059 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2004	4MVXL01.8BBB	1.5, 1.8	Diesel	5000
	FEATURES & EMISSION		TYPICAL EQUIPMENT A	
Inc	direct Diesel Injection, T	urbocharger	Tractor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD		EXHAUST (g/kw-hr)				OPACITY (%)			
	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19≤ KW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			4.1	1.3	0.43	5	3	11

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of May 2003.

Allen Lons, Chief

Mobile Source Operations Division

Engine Model Sur nary Form

ATTACHMENT 1 OF 1

Manufacturer: Mitsubishi Heavy Industries, Ltd.

Engine category: Nonroad CI

EPA Engine Family: 4MVXL01.8BBB

Mfr Family Name: S4L2-T

U-R-035-0059

Process Code: New Submission

	.01			14.3
_ 8		2.		
8.Fuel Rate: 9.Emission Control lbs/hr)@peak torque Device Per SAE J1930	Á.+.),		2	
ŞΨ	IDI TC	DITC	I DI TO	\mathbf{C}
S S	Ĕ	ĭ	١Ľ	DI TC
Ssit	\Box	ᆸ		$\overline{\Box}$
ill s	Ž.	Τ.,		- T
9.E			K	
۵ -				
ē	2.			-12 35
💆	# #		4-5	
e e e	-		\$4E	-
ea E	2	5	, L	7
uel ®p		-	. —	17.8
8.Fuel Rate: hr)@peak to		15.9	15.5	
} !/ Sc			3.5	
€		27.7		1.00
.~	26,8 18			
7.Fuel Rate: nm/stroke@peak forque	150-5	36.0	31.9	33.5
7.Fuel Rate: n/stroke@pe: forque	8	0	G	ıc
Fuel Ra stroke@ torque	9	Ö.		e
trol for	S	ന	က	· CO
7.F n/s		4	1	7,25
Ē				
		, ž	ψ,	
	76.7@2200	98.8@2000		
6.Torque @ RPM (SEA Gross)	76.7@2200	g	Ö	92.9@2400
Forque @ RPI (SEA Gross)	2	8	20	40
@ <u>S</u>	2	8	32	(2)
A (7	8	2	6
ord SE	ဖွ	∞.	82	ું.
3.T		0)	E .	O)
•	72.7	Mary Mary		1
_	18.2		21.0	A
5.Fuel Rate: lbs/hr) @ peak HP (for diesels only)	- 6	., t-==	-	
ak të: onl		1	2.3	
Ra pe	Ś	5	0	_
5.Fuel Rate: s/hr) @ peak or diesels onl	8	22.5	2	22.7
டி இத்	40.4		-	44
5.Fuel Rate: bs/hr) @ peak HF (for diesels only)				
€_	74,7			1
<u>a_</u>			7.	
ate: peak HP only)	7.		,	
es Se Se				
hat Person	Ç.	O.	9	∾:
elf e @	27	34	3	34
4.Fuel R stroke @ or diesel	≘â.∵	1	31 - 20 7 - 20	34.2
4.Fuel Ri mm/stroke @ (for diesel	42	17		- 2-
Ē,			374. 27.	121
=	2		74.4	
				-
3.BHP@RPM (SAE Gross)	8	8	8	8
17. So	õ	Š	8	Ř
3.BHP@RPM (SAE Gross)	0	(9)	(8)	(e)
톲뿧	4	က	က	\sim
3.6	42	49	46	49
			5	. 7.
<u> </u>			140 120	15
þ				
Ž		H	μ.	\vdash
<u> </u>		ġ	4L2-T	2
g.	34	4	4	4
, C	100	נט	ر <u>ن</u>	0)
2.E	÷.			9.7
•	7.2		÷5	1.2
1.Engine Code 2.Engine Model	S4L-Y2T62ST S4L-T	S4L2-Y2TEPA S4L2-T 49.3@3000 34.0	S4L2-Y2T62WM 14 S4L2-T 1 46.9@3000 1 31.	S4L2-Y2T62ST S4L2-T 49.2@3000
B	ST	ď	2	ST
Ŏ	32	Ш	Ñ	62
<u>ج</u>	1	2	H	2T
gi	3	<u>`</u>	١٣.	>
П	<u></u>	3	2	2
-	S	SA	8	S