Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)				
2004 4MVXL02.5AAA		2.3, 2.5	Diesel	5000				
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION					
	Indirect Diesel Inje	ction	Tractor and Industrial Equipment					

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD	-			EXHAUST (g/kw-l		OPACITY (%)			
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19≤ KW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			5.5	1.1	0.35	6	6	9

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

12 TH

day of May 2003.

Allen Lyons, Chief

Mobile Source Operations Division

ATTACHMENT 1 OF 1

Engine Model Sur nary Form

Manufacturer: Mitsubishi Heavy Industries, Ltd.

Engine category: Nonroad CI

EPA Engine Family: 4MVXL02.5AAA

Mir Family Name: SQ-ND

Process Code: New Submission

4-R-035-0061

	* T		÷.,	7			200	·	C, E,				3
9.Emission Control Device Per SAE J1930			陸			1	1+6		3				Ţ
9.Emission Control evice Per SAE J193										4 4			
or S/	ቯ	□	Ξ	□	Ξ	່⊡	□	ቯ	₫	口	Ω	□	
miss Se Pe						9				1		1	1
9.E Jevic		÷ ;									70.		1
			157								1		
e: ord							- 5				6.3		T.L.
Rat	10,02	10.8	14.7	7	12.9	13.9	10.8	14.7	10.2	13.8	10.8	14.6	1
8.Fuel Rate: hr)@peak tor	2	Ť		-	-	¥ + -	Ξ.	7	1	Ť	7	17	ľ
8.Fuel Rate: (lbs/hr)@peak torque		i i i									2		
E	~2.		7.5		75. 75.						- T		1
ea X					-3					ĺ			
7.Fuel Hale: n/stroke@pe torque	34.5	36.5	37	33.5	36.3	35	36,5	37	34.5	35	36.5	7	
-uer Ha troke@ torque	3	36	က	ကိ	36	က	36	က	34	ص	.36	3	L
r.ruel Hale: mm/stroke@peak torque				= :		Ţ				a de la companya de l			
-							4	1					
Σ		0	8	0	Ö	S	÷			Q			1
6.Torque @ RPM (SEA Gross)	94,0@1350	99.5@1350	07ft-lb@1800	92.6@1600	99.8@1600	98ft-lb@1800	99,5@1350	107@1800	94.0@1350	98ft-lb@1800	99.5@1350	107@1800	Linear Control of the
A Gr	00	@ 9	9	(B)	@	B @	@	@	00	b@	(0)	0	
Torq (SE,	94.	99.)7#L	92.	99	9#	99.	107	94.0	-H8	99.	107	
Ġ			_			ြ				6			
۵ _						1	2.4		持		7.7		
o.ruel nate: bs/hr) @ peak HP (for diesels only)		\ (4)						1.5					
en ne Or be sels	13.8	14.8	21.1	18,2	20,4	20.0	14.8	18.3	13.8	20.0	14.8	21.1	1000
o.ruei nate. //hr) @ peak or diesels onl	4 7	-	CV.	-	ر ا	N	7	_	19	N	7	2	
(lbs/	- C Y												
ᇁ			7 - 1 2 1		1.00								100
¥S													
(a) (a) (a) (b) (a) (b) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	35	37	88	32	5.	36	37	38	35	36	37	38	
7.Fuer nate. Nstroke @ pec (for diesel onl	35	37	38		34.5		, , ,		35	Ų,			
mm/stroke @ (for diesel							11.2						7
Ē				<i>i.</i>			36.0hp@1800 37					49.3hp@2500	100
∑ ⊙	8	36.0hp@1800	8	0	0	8	00	0	8	8	8	8	
3.BHP@RPM (SAE Gross)	318	3 18	325	260	270	9.18	3 18	220	ğ 18	325	918	925	
HP(hp()du	hp(5@	5@)du	hp(5@)dh) hp	hp@)dq	(
3.B (S,	33.3	36.0	19.3	41,5@2600	46,	46.0hp@1800	9	44.5@2200	3,3	46.0hp@2500	6.0	9.3	<u>:</u> (
	S4Q 33:3hp@1800	ر. دري. دري	S4O2 👚 19.3hp@2500	,	46,5@2700	`			33,3hp@1800	4	S4Q2-Y265DG 🖟 🐩 S4Q2 💨 36.0hp @ 1800	4	
del	***** *****												. 7
δ	* *	7	5	~	CV:	~	S4Q2 ::	2	. S4O ⊪		C)	5	
ije Lije	34C	S402	40	S4Q	40	S4Q	40	S402	34C	S40	40	S4Q2	٠.
Eng		ွ	ς.··	· ·	S	200	S	S		3,	S	S	
2.1								7			- * / - #		1
1.Engine Code 2.Engine Model	S40-Y261DG	(T	275 C		S4Q2:Y261GT 🖟 🐩 S4Q2 👵				S4Q-Y265DG		(n	C C	
Cod	10G	S4Q2-Y261DG	S4Q2-Y261DP	S4Q-Y261GT	<u>ෆ</u>	S4Q-Y261DP	S4Q2-Y262SD	S4Q2-Y262KL	3DG	S4Q-Y265DP	5D(S4Q2-Y265DP	7
ne	726	Y26	Y26	,26	Y26	,26	Y26	Y26	26	/26	Y26	Y26	5
Ēngi	Ö	75-	32	Ġ	22.	2	22-	02-	Ġ	0	72-	95-	č
1.E	S4	340	Š	S	340	8	340	84	ک	S	54(\$4	ŝ