

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5CPXL10.3ESK	10.3	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler and Engine Control Module			Tractor, Dozer and Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
75≤KW<130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
130≤KW<225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		CERT	--	--	5.0	1.8	0.15	7	1	10

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 7TH day of December 2004.


 Allen Lyons, Chief
 Mobile Source Operations Division

Engine Model Summary Form

U-R-001-0271

Manufacturer: **CATERPILLAR INC.**
 Engine category: **Nonroad Over 50 Hp**
 EPA Engine Family: **5CPXL10.3ESK**
 Mfr Family Name: **N/A**
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
			nominal values.	Due to product-	ion engine avgs.	these fuel rates	may change.	
Note: Peak HP	and Peak torque	fuel rates are						
19	3176/C-10	260 @ 2000	140	94.0	845 @ 1400	166	78.0	EM, DI, TC, ECM,
20	3176/C-10	240 @ 2100	130	92.0	932 @ 1500	184	93.0	EM, DI, TC, ECM,
21	3176/C-10	240 @ 2100	130	92.0	932 @ 1500	184	93.0	EM, DI, TC, ECM,
22	3176/C-10	283 @ 2100	142	101.0	972 @ 1400	185	87.0	EM, DI, TC, ECM,
23	3176/C-10	240 @ 2100	127	90.0	779 @ 1400	150	71.0	EM, DI, TC, ECM,
24	3176/C-10	280 @ 2200	138	102.0	993 @ 1400	185	87.0	EM, DI, TC, ECM,
25	3176/C-10	205 @ 2000	122	82.0	834 @ 1000	164	55.0	EM, DI, TC, ECM,
26	3176/C-10	185 @ 2000	113	76.0	755 @ 1000	148	50.0	EM, DI, TC, ECM,
27	3176/C-10	165 @ 2000	102	69.0	676 @ 1400	132	44.0	EM, DI, TC, ECM,
28	3176/C-10	205 @ 2000	133	89.0	939 @ 1000	187	63.0	EM, DI, TC, ECM,
29	3176/C-10	205 @ 2000	122	82.0	834 @ 1000	164	55.0	EM, DI, TC, ECM,
30	3176/C-10	185 @ 2000	113	76.0	755 @ 1000	148	50.0	EM, DI, TC, ECM,
31	3176/C-10	220 @ 2000	130	88.0	892 @ 1000	177	60.0	EM, DI, TC, ECM,
32	3176/C-10	220 @ 2000	120	80.0	814 @ 1000	160	54.0	EM, DI, TC, ECM,
33	3176/C-10	180 @ 2000	111	74.0	735 @ 1000	144	49.0	EM, DI, TC, ECM,
34	3176/C-10	240 @ 2000	140	94.0	971 @ 1000	195	66.0	EM, DI, TC, ECM,
35	3176/C-10	220 @ 2000	130	88.0	892 @ 1000	177	60.0	EM, DI, TC, ECM,
36	3176/C-10	200 @ 2000	120	80.0	814 @ 1000	160	54.0	EM, DI, TC, ECM,
37	3176/C-10	240 @ 2000	140	94.0	971 @ 1000	195	66.0	EM, DI, TC, ECM,
38	3176/C-10	220 @ 2000	130	88.0	892 @ 1000	177	60.0	EM, DI, TC, ECM,
39	3176/C-10	165 @ 2000	102	69.0	676 @ 1000	132	44.0	EM, DI, TC, ECM,
40	3176/C-10	180 @ 2000	111	74.0	735 @ 1000	144	49.0	EM, DI, TC, ECM,
41	3176/C-10	250 @ 2100	125	88.1	813 @ 1600	162	86.9	EM, DI, TC, ECM,
42	3176/C-10	270 @ 2100	136	91.9	878 @ 1600	174	95.1	EM, DI, TC, ECM,
45	3176/C-10	258 @ 2100	130	92.1	932 @ 1500	184	92.9	EM, DI, TC, ECM,
46	3176/C-10	258 @ 2100	130	92.1	932 @ 1500	184	92.9	EM, DI, TC, ECM,