Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2005	5X9XL0359AAK	5.9	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS						
Direct Diesel Injection, Turbocharger, Charge Air Cooler			Crane, Loader, Tractor, Dozer, Pump and Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS	CATEGORY		НС	NOx	NMHC+NOx	со	РМ	ACCEL	LUG	PEAK
75 <u><</u> kW < 130	Tier 2	STD	N/A	N/A	6.6	5.0	0.30	20	15	50
130 <u><</u> kW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		FEL	N/A	N/A	8.9	N/A	0.30	N/A	N/A	N/A
		CERT			7.2	0.8	0.18	6	1	22

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order

Executed at El Monte, California on this ______ day of November 2004.

Enfall Susport

Allen Lyons, Chief Mobile Source Operations Division

Engine Model Summary Form ATTACHMENT Pg 1 of 1

CNH Engine Corporation 5X9XL0359AAK Nonroad CI Mfr Family Name: L403 EPA Engine Famly. Engine category: Manufacturer:

New Submission

Process Code:

U-R-011-0089

Z

Ť		
봋		
Sec. 3		69
7.Fuel Rate: m/stroke@peal torque	112 104	
uel Ra troke@ torque		6
to the		
7.F n/s		ξ
Ē		
	888.5	þ
Σ	593@1500 550@1500	0
RP (S	ုင္လုိုင္က	õ
@, Ĕ	T T	ч.) —
- G	ଇ ବ	0
3.Torque @ RPM (SEA Gross)	500	612@1500
(S	പറ	ഹ
6.		3. í
		63
۵.		
. <u>+ 2</u>		
on ak	_	
8 g %	<u> </u>	4
5.Fuel Rate: /hr) @ peak or diesels ont	77.1 71.9	80
ਧੁੱਠੂ ਤੋਂ		
5.Fuel Rate: tbs/hr) @ peak HP (for diesets only)		
E),		æ
0		
÷		
~ 놂 오		
pe on		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5 9	-
uel (e	Υ ∞	.
ЕĘР		
Vst 4 (fo		
JUL I	2018 - 12 2018 - 12	è
_		
N (s	200@2500 185@2500	0
RF os	N N	20
මලි	A A	Ň
3.BHP@RPM (SAE Gross)	S S	65@2200
S/S/	000	3
(1) -		
		22
e		2.4
Model		<u></u>
Σ	6	ğ
e	မှု မှု	ц
<u>a</u> .	A A	P.
Ĕ	61	6TA-59
<u> </u>	6TA-590 6TA-590	
		<u>e</u>
de	H 8	Ø
ŏ	N N	6
Š	600	90
пe	μ μ	Ĕ
ē	지 물건없이 드는 사람	Щ
	<u> </u>	8
Ш	89;I	20
1.Engine Code 2.Engine N	1889;FR90001 1889;FR9898	1962
1.En	1889;FR90001 1889,FR9898	1962;FR90018
1.En	1889;1	1962

8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930

DDI,TC,CAC DDI,TC,CAC DDI,TC,CAC

56.8 52.5

48,9