CNH ENGINE CORPORATION, INC.

EXECUTIVE ORDER U-R-011-0091 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)	
2005	5X9XL0505AAB	8.3	Diesel	8000	
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION		
Direct Dies	el Injection, Turbocharg	er, Charge Air Cooler	Crane, Loader, Tractor, Dozer	, Pump, Compressor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED EMISSION POWER STANDARD			EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
130 ≤ kW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	20	15	50
		FEL	N/A	N/A	8.7	N/A	0.25	N/A	N/A	N/A
		CERT			8.3	0.7	0.22	9	5	28

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of November 2004.

Allen Lyons, Chief

Mobile Source Operations Division

Rephael Surverity

Engine Model Summary Form ATTACHMENT (2 (o.f.)

W-R-0(1-0091

Manufacturer: CNH Engine Corporation

Engine category: Nonroad CI

EPA Engine Family: 5X9XL0505AAB

Mir Family Name: K413

Process Code: New Submission

	DDI,TC, CAG			
8.Fuel Rate: 9.Emission ConIrol (lbs/hr)@peak torque Device Per SAE J1930				1.7
9.Emission Control evice Per SAE J193	O	ပ	()	
<u> </u>	⋖	DDI,TC, CAC	DDI,TC,CAC	
0.8	U	$^{\circ}$	O	
no s	ပ	S	Ş	
Pe	- t-	: H		
e E			0	
a. Š		ୁଠା		
ے د				
Ð				
。	MOST A			
: Š	2000 3000 3000 3000			
8.Fuel Rate: hr)@peak tor	89.1	89.1	83.9	
ea H	G	တ	6	
an de	ω	ထ	$\boldsymbol{\omega}$	
ي ≅				
8,4%		3		
<u>ē</u>				
_				
¥				. 1
:				
age G	(C)	ഹ	m	
7.Fuel Rate: nn/stroke@peak torque	176	176	Ö	
e de la	7.5	FT.	1	
⊡ ¥s		K. H		
7 [2]	1000			
=		(and S		
_				
≥ .	0	0	0	Mar 6
ES (2)	Q	2	S	
@ 2		<u> </u>	-	
Torque @ RPP (SEA Gross)	944@1500	944@1500	853@1500	
లేయ్	3	7	33	
<u> S</u> <u>S</u>	ેં	ð	ထ	
6.Torque @ RPM (SEA Gross)				()
				* 1
_				ing s
ΪS		er.y		
9 X E	, 4			
s c se	Q	101.0	N	8
2 G 3	Ξ	Ξ	98.2	
ië (e	-	\vdash	О.	
5.Fuel Rate: bs/hr) @ peak Hf (for diesels only)	101.0		30	A 17
5.Fuel Rate: (bs/hr) @ peak HP (for diesels only)				
5	lage V	100		i o t
<u>α</u>				
4.Fuel Rate: mm/stroke @ peak HP (for diesel onty)	20 Mg			
ः हं ≥	U.S.			
4.Fuel Rate: Vstroke @ peak (for diesel onty)				
4.Fuel Ra stroke @ p or diesel o	136	136	က	. 8
e e		· -		
드등				
A st 6				
Ę		2007 J 1		21 NOVEMBER 1882
	100000000000000000000000000000000000000			
=				
=	400			
	0	0	0	
	200	200	200	
	12200	2200	2200	
	@2200	@2200	@2200	
	30@2200	30@2200	50@2200	
3.BHP@RPM II (SAE Gross)	280@2200	280@2200	250@2200	
	280@2200	280@2200	250@2200	
	280@2200	280@2200	250@2200	
3.ВНР@RPM (SAE Gross)	280@2200	280@2200	250@2200	
3.ВНР@RPM (SAE Gross)	280@2200			
3.ВНР@RPM (SAE Gross)				
3.ВНР@RPM (SAE Gross)	6TAA-830 280@2200			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
3.ВНР@RPM (SAE Gross)	6TAA-830			
		8222;FR91251 6TAA-830 280@2200	8185;FR90884 6TAA-830 250@2200	