IVECO N.V.

EXECUTIVE ORDER U-R-015-0059

New Off-Road
Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5VEXL06.7DGA	6.7	Diesel	8000
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT A	APPLICATION
Direct Dies	sel Injection, Turbocharg	er, Charge Air Cooler	Generator S	et

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD				XHAUST (g/kw-ł	or)		OI	PACITY (%	(o)
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
130 ≤ kW < 225	Tier 2	STD	N/A	N/A	6.6	3.5	0.20	N/A	N/A	N/A
		CERT			6.2	1.0	0.16	-	_	-

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of January 2005.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Sur 1ry Form AMAGINEN PS (OF I

unufacturer: IVECO NV

gine category: Nonroad CI

A Engine Family: 6VEXL06.7DGA

ir Family Name: F4GE0685

ocess Code: New Submission

8.Fuel Rate: 9.Emission Control (lbs/hr)@peak forque Device Per SAE J1930	DUT, EM. TAA. CAC EM. TAA. EM. TAA. EM. TAA.
8.Fuel Rate: (lbs/hr)@peak forg	N N N N N N N N N N N N N N N N N N N
	A N N N N N N N N N N N N N N N N N N N
7.Fuel Rate: 6.Torque @ RPM mm/stroke@peal (SEA Gross) torque	681@ 1800 673 @ 1800 733 @ 1500 679 @ 1800 611 @ 1500
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	N/A N/A N/A N/A
4 Fuel Rate: mrn/stroke @ peak HP (for dlesel only)	N/A F4GE0685F*F 233 @ 1800 141 N/A N/A F4GE0685A*F 231 @ 1800 140 N/A N/A F4GE0685B*F 209 @ 1500 140 N/A N/A F4GE0685C*F 198 @ 1800 118 N/A N/A F4GE0685D*F 174 @ 1500 128 N/A
3.BHP@RPM (SAE Gross)	233 @ 1800 231 @ 1800 209 @ 1500 198 @ 1800 174 @ 1500
2.Engine Model	F4GE0685F*F F4GE0685A*F F4GE0685B*F F4GE0685C*F F4GE0685D*F
Engine Code	N/A N/A N/A N/A N/A

Engine Model Summary Form ATTACHMENT BLOF 2

12-8-015-0059

IVECO NV Janufacturer:

Nonroad Cl Ingine category: 5VEXL06.7DGA ∃PA Engine Family.

Mfr Family Name:

Running Change Process Code:

Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4. Fuel Rate: 5. Fuel Rate: mm/stroke @ peak HP (lbs/hr) @ peak HP (for diesel only) (for diesels only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930
¥ Z	F4GE0485A*F		139.2		460			DDI, EH, TAA, CAC
ΑN	F4GE0485B*F	148@1800	132		579			
ΝΑ	F4GE0485C*F	117,5@1500	121.5		409			
ΝΑ	F4GE0485D*F	130@1800	114.5		384			•