California Environmental Protection Agency AIR RESOURCES BOARD

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5KBXL01.5FAD	1.499	Diesel	5000
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT A	
Inc	direct Diesel Injection, T Smoke Puff Limiter (Son	urbocharger, ne Models)	Loader	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION			E	XHAUST (g/kW-	hr)		OF	PACITY (%	•)
CLASS	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
19 <u>&lt;</u> kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			5.9	0.7	0.26	5	3	15

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of October 2004.

Allen Vons, Chief Mobile Source Operations Division

## **Engine Model Summary Form**

Manufacturer: KUBOTA Corporation Engine category: Nonroad CI EPA Engine Famy. 5KBXL01.5FAD Mfr Family Name: N/A

Marhuart U-N-025-0187

Process Code: Running Change

D1503-M-T-ES 44.7@2800 40.0 18.8 101.4@1700 46.2 13.2   D1503-M-T-ES 44.7@2800 40.0 18.8 101.4@1700 46.2 13.2   D1503-M-T-ES 44.7@2800 39.2 17.1 93.5@1600 43.3 11.6   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6   D1503-M-T-ES 35.0@2300 37.2 14.3 91.5@1600 42.4 11.4	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
D1503-M-T-ES 44.7@2800 40.0 18.8 101.4@1700 46.2 13.2 1   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6 1   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6 1   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6 1   D1503-M-T-ES 35.0@2300 37.2 14.3 91.5@1600 42.4 11.4 1	D1503-M-T-ES01	D1503-M-T-ES	44.7@2800	40.0	18.8	101.4@1700	46.2	13.2	LEA MA
D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6   D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6 3   D1503-M-T-ES 35.0@2300 37.2 14.3 91.5@1600 42.4 11.4 1	1-T-ES01b		44.7@2800	40.0	18.8	101.4@1700	46.2	13.2	SPL
D1503-M-T-ES 40.0@2600 39.2 17.1 93.5@1600 43.3 11.6 D1503-M-T-ES 35.0@2300 37.2 14.3 91.5@1600 42.4 11.4	D1503-M-T-ES02	D1503-M-T-ES	40.0@2600	39.2	. 17.1	93.5@1600	43.3	11.6	NA
35.0@2300 37.2 14.3 91.5@1600 42.4 11.4	A-T-ES02b		40.0@2600	39.2	17.1	93.5@1600	43.3	11.6	SPL
	A-T-ES03b		35.0@2300	37.2	14.3	91.5@1600	42.4	11.4	SPL