Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003:

IT IS/ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2005	5KBXL02.4FCC	1.826, 2.434	Diesel	3000, 5000						
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
	Indirect Diesel Inje	ction	Generator S	Set						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC). oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION		-	E	EXHAUST (g/kW-ł		OPACITY (%)					
	STANDARD CATEGORY		нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK		
8 <u><</u> kW < 19	Tier 2	STD	N/A	N/A	7.5	6.6	0.80	N/A	N/A	N/A		
19 <u>≤</u> kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	N/A	N/A	N/A		
		CERT			5.9	1.3	0.26					

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of October 2004.

ons, Chief Mobile Source Operations Division

Engine Model Sr Amary Form

KUBOTA Corporation New Submission EPA Engine Family 5KBXL02.4FCC Nonroad Cl Mfr Family Name: N/A Engine category: Process Code: Manufacturer:

Attachment 1 of 1 U-R-025-0200 4

Ō														÷						1
1 <u>9</u>	A	<u> </u>																	÷	÷
VE J		. •												:				<u>.</u>		:
ion r S/	V N VN VN	¥¥-			-	:						-		. ~ \						1
niss 9 Pe	4 4 4	4			:											-				
9.Emission Control Device Per SAE J1930												-		:				•		-
De													•	1						1
ent					-					-		:				-		:		
8.Fuel Rate: (lbs/hr)@peak torque														;			:	•	1	
8.Fuel Rate: hr)@peak tor	A N A N	N/A										:	:					•		:
Fue 0,00	~ ~ ~	~								•			:							
s/hr																			1	
Ð												-		: :						:
<u>육</u>												:					•	:		÷
7.Fuel Rate: mm/stroke@peak torque		_			•					•										
⁼ uel Rat stroke@ torque	N/A N/A	N/A																:	÷	÷
.Fu /stre to	-													:	:			:		1
L PE									•									:		÷
											•	•		1		}		:	-	
Σ												:		•		:		:	-	:
6.Torque @ RPM (SEA Gross)		_			•			:			:			•		-			+	-
6 6 C C	A N A N	N/A																		
orqu SEA		_					•							:		:	:	:	-	
6.T. (;																				
												•							-	
ξŢ			•		:							:				:				
ate: eak : onl	_ ~	~+																•	:	
el P Sels	12.1 9.9 16.4	13.4										:				:				•
5.Fuel Rate: (Ibs/hr) @ peak HP (for diesels only)		τ-			:							:							-	:
3 (lbs/					:							:							÷	
												:		÷	:					•
Ξ ×														:			•		-	-
4.Fuel Rate: v/stroke @ peak HP (for diesel only)	ဝပထ	0				· ·				:		:					1		:	
el R asel	40.0 39.5 40.5	40.0								-		÷		:		:	:	•		
r die	- • • •	•			:									•			:	;	:	
4.Fuel F mm/stroke @ (for diese					•					:									:	
E								1						-				1	;	
~		80												:						
APN oss)	916 915 916	315												•						
0 Ū	29.9@1800 25.1@1500 40.0@1800	33.9@1500																	:	
SAE	້29 25 25 25	33								:									:	
3.BHP@RPM el (SAE Gross)	D1803-M-BG-ES ^{+ W} 29.9@1800 D1803-M-BG-ES <i>1</i> y.725.1@1500 V2403-M-BG-ES <i>29,8</i> 40.0@1800															:				
leb	ស អ ស	ËS																		-
Ň	ė ė ė	В										•								
ре	D1803-M-BG-ES D1803-M-BG-ES V2403-M-BG-ES	V2403-M-BG-ES										•								
ŋgr	803 803 403	403			:															
2.Engine Model	2 D J	V2																		
	301 302 301	302																		
1.Engine Code	D1803-M-BG-ES01 D1803-M-BG-ES02 V2403-M-BG-ES01	V2403-M-BG-ES02																		
ŏ		-BG																	-	
ine	× × ×	Э-М-																		
Ő	S S S	400																		
5	<u> </u>																			

⊁