ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0116

New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2005	5H3XL1.00SCV	1.005	Diesel	3000		
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
	Indirect Diesel Inje	ection	Tractor and Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION	EXHAUST (g/kw-hr)				OPACITY (%)				
CLASS	STANDARD		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
8 <u><</u> KW<19	Tier 2	STD	N/A	N/A	7.5	6.6	0.80	20	15	50
		CERT			3.6	2.5	0.36	8	14	12

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 25th day of December 2004.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Summary Form

9110-920-21-11

Manufacturer: Ishikawajima-Shibaura Machinery Co., Ltd.

Engine category: Nonroad CI

EPA Engine Family: 5H3XL1.00SCV

Mfr Family Name: N/A

Process Code: New Submission

		2872738 8873738	600363 8+1363	
30				
Sontro				
ion C r SAE	Œ	正	₫.	正
9.EmIssion Control Device Per SAE J1930				
9.E Jevic				
te: torqt	₹	₹.	ĸ.	5
8,Fuel Rate; lbs/hr)@peak torque	8.1+/-0.4	8,1+/-0,4	8.9+/-0.5	8.9+/-0.5
3.Fue	ω	8	8	о. •
//sq/)				
7.Fuel Rate: mm/stroke@peak torque	(X)	7.5	ري -	22.4+/-1.2
7.Fuel Rate: n/stroke@pe torque	22.3+/-1.2	22.3+/-1.2	22,4+/-1.2	4+/-
7.Fu m/stn to	2	ä	CZ.	8
Ē				
_				_
RPN iss)	20C	200	400	.40C
s.Torque @ RPM (SEA Gross)	44,5@2200	44.5@2200	44.3@2400	44,3@2400
Forqu (SEA	4	44	7	44.
69				
Ē_				
ate: ∍ak ⊁ onlyj	10.1+/-0.5	10.1+/-0.5	11,1+/-0.5	0.5
5.Fuel Rate: s/hr) @ peak or diesels onl	7) +	≯	11,1+/-0,5
5,Fuel Rate: lbs/hr) @ peak HP (for diesels only)	0	0	. 	F
ਰ ਹ				
Ţ	19933			
ate: peak only)	0	0	, ()	-0
4.Fuel Rate: stroke @ pea for diesel only	21.4+/-1.0	\ \ \	; 	21,7+/-1.0
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	2	2	21.7+/-1.0	21
Ē				
RPM oss)	850	850	100) -
s.BHP@RPM (SAE Gross)	23.0@2850	23.0@2850	25.0@3100	25.0@3100
3.B	23.	23.0	25.(25.
			f 1	
lel				
Mo	20	80	8	φ ₀
jine	23/2850	285	25/3100	25/3100A
Enç	ÈΫ	23.	સં	R)
2				
1.Engine Code 2.Engine Model	YARDA NGC			
S	Ç	Ç	ပ	φ
gine	S773-C	773	S773-0	S773-C
Ω̈́	భ	ഗ	တ	တ
_	Gest.	وو		
		بيطى		400