

## ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0117 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2005	5H3XL1.13MSL	1.131	Diesel	5000			
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
Indirect Diesel Injection			Loader				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 <u>&lt;</u> KW<37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			4.5	1.5	0.36	7	6	12

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Raphael Lunowith

Executed at El Monte, California on this \_\_\_\_\_\_\_ 25<sup>24</sup>\_\_\_\_\_ day of December 2004.

Allen Lyons, Chief

Mobile Source Operations Division

## Engine Model Summary Form

U-R-026-0117

Ishikawajima-Shibaura Machinery Co., Ltd. Manufacturer:

5H3XL1.13MSL Nonroad Cl Engine category:

EPA Engine Famiy.

Mfr Family Name:

New Submission Process Code:

strol J1930	4				900000			
9.Emission Control Device Per SAE J1930	⋢	╚	正	≖	⊑	Ξ	E	
8.Fuel Rate: (lbs/hr)@peak torque _E	8.3+/-0.5	8.7+/-0.5	2.0-/+7.6	9'0-/+9'6	8.5+/-0.5	8.5+/-0.5	6.0-/+8.6	
7.Fuel Rate: mm/stroke@peak torque	24.0+/-1.5	22.9+/-1.4	25.54-1.7	24,4+/-1,5	23.5+/-1.4	23,5+/-1,4	23.5+/-1.3	
6.Torque @ RPM {SEA Gross)	49.3@2100	48.8@2300	51.9@2300	50.2@2400	50.2@2200	50.2@2200	51,6@2400	
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	12.2+/-0.7	11,6+/-0.9	12,6+/-0.8	13,4+/-0.9	9'0"/+6'01	10:9+/-0:0	12,7+/-03	
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	24.6+/-1.5	19.5+/-1.4	22.6+/-1.5	22:6+/-1,5	23.1+/-1,2	23.1+/-1.2	22.0+1-0.6	
3.BHP@RPM (SAE Gross)	26.4@3000	25,6@3600	28.2@3400	29.9@3600	26.0@2850	26.0@2850	29 1@3500	
2.Engine Model	HH26/3000	HH26/3600	HH28/3400	HH30/3600	26/2850	26/2850A	29/3500	
Engine Code	403C-11	403C-11	403C-11	4030-11	S773L-C	S773L-C	S773L-C	