 AIR RESOURCES BOARD	ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.	EXECUTIVE ORDER U-R-026-0122
		New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5H3XL2.00N84	1.496 and 1.995	Diesel	5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Indirect Diesel Injection			Loader, Tractor and Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
19≤KW<37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	3.7	2.1	0.34	5	5	8

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 29TH day of December 2004.


 for Allen Lyons, Chief
 Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: **Isnikawajima-Shibaura Machinery Co., Ltd.**

Engine category: **Nonroad CI**

EPA Engine Family: **5H3XL2.00N84**

Mfr Family Name:

Process Code: **Running Change**

U-R-026-0122

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
403C-15	HL28/2200	27.8@2200	31.1+/-2.1	11.3+/-0.8	70.8@1800	33.5+/-2.7	9.9+/-0.8	FI
403C-15	HL28/2200J	28.0@2200	31.2+/-2.1	11.3+/-0.8	70.8@1800	33.5+/-2.7	9.9+/-0.8	FI
403C-15	HL30/2400	29.9@2400	31.1+/-2.1	12.3+/-0.8	70.8@1800	33.5+/-2.7	9.9+/-0.8	FI
403C-15	HL31/2600	31.4@2600	31.1+/-2.1	13.3+/-0.9	70.8@1800	33.5+/-2.7	9.9+/-0.8	FI
403C-15	HL32/3000	32.1@3000	28.9+/-1.8	14.3+/-0.9	63.7@1800	29.0+/-1.4	8.6+/-0.4	FI
403C-15	HL33/2800	32.7@2800	30.0+/-1.8	13.8+/-0.8	70.8@1800	32.9+/-2.7	9.9+/-0.8	FI
403C-15	HL34/3000	33.7@3000	29.6+/-1.8	14.6+/-0.9	70.8@1800	32.9+/-2.7	9.9+/-0.8	FI
N843-C	30/2400-20XT	30.0@2400	32.2+/-1.8	12.7+/-0.7	70.9@1800	34.3+/-2.4	10.2+/-0.7	FI
N843-C	31/2600-C2	31.0@2600	31.4+/-1.6	13.5+/-0.7	72.0@1800	34.3+/-2.5	10.2+/-0.7	FI
N843-C	32/2900-LS140	32.1@2900	29.2+/-1.8	13.9+/-0.9	71.2@1700	34.0+/-2.0	9.5+/-0.6	FI
N843-C	38/3200-LS160	38.0@3200	32.7+/-1.9	17.2+/-1.0	75.5@2000	34.9+/-2.0	11.5+/-0.7	FI
N843-C	TC30/2600	30.0@2600	29.5+/-1.8	12.6+/-0.8	69.7@1700	34.2+/-2.0	9.6+/-0.6	FI
N843-C	TC33/2800	33.0@2800	32.6+/-1.6	15.0+/-0.8	73.0@2000	35.5+/-2.5	11.7+/-0.8	FI
N844-C	40/2800	40.0@2800	28.6+/-2.1	17.6+/-1.3	79.7@2200	27.1+/-1.8	13.7+/-0.9	FI
N844-C	46/2900-LS160	46.0@2900	32.3+/-1.7	20.6+/-1.1	97.0@1800	35.5+/-1.8	14.0+/-0.7	FI
N844-C	TC40/2600	40.0@2600	30.7+/-1.6	17.5+/-0.9	97.4@1800	35.2+/-1.7	13.9+/-0.7	FI
S3L3	30/2600-Y211RH	30.0@2600	29.5+/-1.8	12.6+/-0.8	69.7@1700	34.2+/-2.0	9.6+/-0.6	FI