

ISHIKAWAJIMA-SHIBAURA MACHINERY CO., LTD.

EXECUTIVE ORDER U-R-026-0135 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2005	5H3XL2.22NLT	2.216	Diesel	5000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS		CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION			
Indirect Diesel Injection, Turbocharger			Generator			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kw-hr)			OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
19 <u><</u> KW<37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	N/A	N/A	N/A
		CERT			5.3	0.8	0.39			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 574 day of January 2005

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Summary Form

Ishikawajima-Shibaura Machinery Co., Ltd. Manufacturer:

Nonroad CI Engine category:

5H3XL2.22NLT EPA Engine Family.

U-R-026-0135

Mfr Family Name: N/A

New Submission Process Code:

30	1		
8.Fuel Rate: 9.Emission Control lbs/hr)@peak torque Device Per SAE J1930	Œ	? ?	
sion C er SA	正	正	
≡miss ice Pe		:	
9.I Devi			•
rque	₹ .		
8.Fuel Rate: hr)@peak tor	15.6+/-1.4	,	
Fuel @pe	5.6	z	
8. Ibs/hr			
× 			
7.Fuel Rate: nm/stroke@peak torque	47.2+/-4.2	-	
7.Fuel Rate: n/stroke@pe torque	7.2+/	Ž	
7.F nm/st	4		
_			1
KPM (s	200		*
6.Torque @ RPM (SEA Gross)	30.5@1500	₹	
orque	30.5	_	
6.1			
Ē ≥		18.2+/-1.5 N/A N/A N/A	
5.Fuei Rate: lbs/hr) @ peak HP (for diesels only)	18.2+/-1.5	18.2+/-1.5	
5.Fuel Rate; s/hr) @ peak or or diesels only	8.2+/-1.5	3.2+,	
5.8 (lbs/hi (for (÷	÷	
<u>₽</u>			
4.Fuel Rate: //stroke @ peak F (for diesel only)	46.1+/-3.7	46.1+/-3.7	
4.Fuel Rate: mm/stroke @ peak ł (for diesel only)	46,1+/-3.7	1+/	
4.Fue stroke or die	46.	46.	
rmm/s (f		:	
5	0	0	
@RPN Sross)	180	180	
3.BHP@RPM (SAE Gross)	7@	44.7@1800	
3.1	44	4	98 15
<u></u>	. N.		
Jode	00	HR45/1800C	
ле Г	5/18	5/18(
Engi	HR4	IR45	
1.Engine Code 2.Engine Model	404C-22T HR45/1800 44.7@1800	404C-22T HR45/1800C 44.7@180	
apo			
e Cc	22T	.22T	
ngín	74C	404C-22T	
<u>т</u>	4	4	