

 AIR RESOURCES BOARD	MOTORENFABRIK HATZ GMBH & CO. KG	EXECUTIVE ORDER U-R-034-0081 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5HZXL347V30	0.347	Diesel	3000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection			Pump, Compressor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
kW < 8	Tier 2	STD	N/A	N/A	7.5	8.0	0.60	N/A	N/A	N/A
		CERT	--	--	6.1	4.9	0.63	--	--	--

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 24TH day of March 2005.


 Allen Lyons, Chief
 Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: **Motorenfabrik Hatz**
 Engine category: **Nonroad CI**
 EPA Engine Family: **5HZXL347V30**
 Mfr Family Name: **1B30 V**
 Process Code: **New Submission**

Attachment 1 of 2
U-R-034-0081

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
N/A	1B30 V	6,7@3600	16	3,2	12,1@2000	16	1,8	DD7
N/A	1B30 V	6,7@3550	16	3,2	12,1@2000	16	1,8	
N/A	1B30 V	6,6@3500	16	3,1	12,1@2000	16	1,8	
N/A	1B30 V	6,6@3450	16	3,1	12,1@2000	16	1,8	
N/A	1B30 V	6,6@3400	16	3,0	12,1@2000	16	1,8	
N/A	1B30 V	6,5@3350	16	3,0	12,1@2000	16	1,8	
N/A	1B30 V	6,5@3300	16	2,9	12,1@2000	16	1,8	
N/A	1B30 V	6,5@3250	16	2,9	12,1@2000	16	1,8	
N/A	1B30 V	6,4@3200	16	2,9	12,1@2000	16	1,8	
N/A	1B30 V	6,4@3150	16	2,8	12,1@2000	16	1,8	
N/A	1B30 V	6,3@3100	16	2,8	12,1@2000	16	1,8	
N/A	1B30 V	6,3@3050	16	2,7	12,1@2000	16	1,8	
N/A	1B30 V	6,2@3000	16,5	2,8	12,1@2000	16,5	1,8	
N/A	1B30 V	6,2@2950	16,5	2,7	12,1@2000	16,5	1,8	
N/A	1B30 V	6,1@2900	16,5	2,7	12,1@2000	16,5	1,8	
N/A	1B30 V	6,0@2850	16,5	2,6	12,1@2000	16,5	1,8	
N/A	1B30 V	6,0@2800	16,5	2,6	12,1@2000	16,5	1,8	
N/A	1B30 V	5,9@2750	16,5	2,5	12,1@2000	16,5	1,8	
N/A	1B30 V	5,8@2700	16,5	2,5	12,1@2000	16,5	1,8	
N/A	1B30 V	5,8@2650	16,5	2,4	12,1@2000	16,5	1,8	
N/A	1B30 V	5,7@2600	16,5	2,4	12,1@2000	16,5	1,8	
N/A	1B30 V	5,6@2550	16,5	2,3	12,1@2000	16,5	1,8	
N/A	1B30 V	5,5@2500	16,5	2,3	12,1@2000	16,5	1,8	
N/A	1B30 V	5,4@2450	16,5	2,3	12,1@2000	16,5	1,8	
N/A	1B30 V	5,4@2400	16,5	2,2	12,1@2000	16,5	1,8	
N/A	1B30 V	5,3@2350	16,5	2,2	12,1@2000	16,5	1,8	
N/A	1B30 V	5,2@2300	16,5	2,1	12,1@2000	16,5	1,8	
N/A	1B30 V	5,1@2250	16,5	2,1	12,1@2000	16,5	1,8	
N/A	1B30 V	5,0@2200	16,5	2,0	12,1@2000	16,5	1,8	
N/A	1B30 V	4,9@2150	16,5	2,0	12,1@2000	16,5	1,8	
N/A	1B30 V	4,8@2100	16,5	1,9	12,1@2000	16,5	1,8	

N/A
N/A
1B30 /N
1B30 /N
4,7@2050
4,6@2000
16,5
16,5
1
1,8
12,1@2000
12,1@2000
16,5
16,5
1,8
1,8

U-R-034-0081

Attachment 2 of 2