

 AIR RESOURCES BOARD	MOTORENFABRIK HATZ GMBH & CO. KG	EXECUTIVE ORDER U-R-034-0083-1
		New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2005	5HZXL462V40	0.462	Diesel	3000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection			Pump, Compressor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
kW < 8	Tier 2	STD	N/A	N/A	7.5	8.0	0.80	N/A	N/A	N/A
		CERT	--	--	6.2	5.4	0.49	--	--	--


BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-R-034-0083 dated March 24, 2005.

Executed at El Monte, California on this 25th day of May 2005.


 Allen Lyons, Chief
 Mobile Source Operations Division

Engine Model Summary Form

Attachment 1 of 2
U-R-034-0083

Manufacturer: **Motorenfabrik Hatz**
 Engine category: **Nonroad CI**
 PA Engine Family: **5HZXL-462V40**
 Mfr. Family Name: **1B40 T/U/W/W**
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
N/A	1B40 T/U/W/W	9,8@3600	24	4,8	17,5@2250	25	3,1	DDF
N/A	1B40 T/U/W/W	9,7@3550	24	4,7	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,7@3500	24	4,7	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,6@3450	24	4,6	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,6@3400	24	4,5	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,6@3350	24	4,5	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,5@3300	24,5	4,5	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,4@3250	24,5	4,4	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,4@3200	24,5	4,4	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,3@3150	24,5	4,3	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,2@3100	24,5	4,2	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,2@3050	24,5	4,2	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,1@3000	25	4,2	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,0@2950	25	4,1	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	9,0@2900	25	4,0	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,9@2850	25	4,0	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,8@2800	25	3,9	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,7@2750	25	3,8	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,6@2700	25	3,8	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,5@2650	25	3,7	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,4@2600	25	3,6	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,3@2550	25	3,6	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,1@2500	25	3,5	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	8,0@2450	25	3,4	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	7,9@2400	25	3,3	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	7,8@2350	25	3,3	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	7,6@2300	25	3,2	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	7,5@2250	25	3,1	17,5@2250	25	3,1	
N/A	1B40 T/U/W/W	7,3@2200	25	3,1	17,5@2200	25	3,1	
N/A	1B40 T/U/W/W	7,1@2150	25	3,0	17,5@2150	25	3,0	
N/A	1B40 T/U/W/W	6,9@2100	25	2,9	17,5@2100	25	2,9	

UW+

25

25

2,9
2,8

17,4@2050
17,4@2000

2,
2,8

25
25

6,8@2050
6,6@2000

1B40 T/U/W/W
1B40 T/U/W/W

N/A
N/A

U R-034-0083

Attachment 2 of 2

J