

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
5MVXL01.5CCC	1.5	Diesel							
ATURES & EMISSION (CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
ct Diesel Injection, Tu	ırbocharger	Tractor							
	5MVXL01.5CCC	(liters)	5MVXL01.5CCC 1.5 Diesel ATURES & EMISSION CONTROL SYSTEMS TYPICAL EQUIPMENT A						

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	EXHAUST (g/kw-ł	hr)		Of	PACITY (%	o)
POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
19 ≤ KW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			7.3	2.4	0.45	15	14	25

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

Allen Lyons, Chief

Mobile Source Operations Division

day of December 2004.

Engine Model Sr. mary Form

1510-58-0151

Manufacturer: Mitsubishi Heavy Industries, LTD.

Engine category: Nonroad CI

EPA Engine Family: 5MVXL01.5CCC

Mfr Family Name: K3M-DT

Process Code: New Submission

	4								4.				일은					ر انتاجات	1.5		45.00				•
30		T					772, 121 127	Va., 1			F				Ī]=								
8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930		}						2			. :[Ť			M							.
n Cc SAE	5	ည	5	5	ည	5		3.5					. •		1						1				
ssio Per	DI,TC	<u></u>	DI,TC	DI,TC	DI,TC	DI,TC							-				ŀ				ĺ				
Emi ice 1					2/04 2/04 2/04			[*							: 1						. [
9. Dev		ļ				İ															į		ļ.	- Te	. !
e																	İ								
e: Ord	3		š															4.4							
Rate sak 1	9.0	9.3	9.0	9.2	9,8	9.2	-							~	į.						.				
uel @pe	တ	6	6	0	G	6		#0 74						£ 3.1											:
8.F /hr)															į.					: Å2 1 17			ľ		4
sqI)					. 5										ું		į						<u>i.</u>		:
×	-												1										1		:
7.Fuel Rate: mm/stroke@peak torque											ŀ	1		i va	7.								1		;
7.Fuel Rate: n/stroke@pe torque	34.2	د	31.3	31	33	3									Ì					-			l.		
Fuel strok tore	က	က	က							2.77 .43										- 1					
Junu					3.5			- X										=		:=				* [] 	
_							18° 1			(2.5) (2.5)	ļ	31		5.3			ŀ								
5		_						10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to 10 to			· ·				-								. [4
6.Torque @ RPM (SEA Gross)	75.7@1600	72.3@1800	65.8@1800	70.2@1800	75.2@1800	70.2@1800												Ţ.							
6 0 0	8	(6)	9	9	0	9					.				*****				:	22			3.24	44	
rque EA (5.7	<u>ب</u>	5.8	.2	2.5).2		7 (2)															٦		
oT.c	7	72	Ö	×	1	۲					ļ			7-3				- 1			-				
Ů.								1 1 22		F.							j								
₽~	1		la e Mark													17									
ak F			13 E																	-			٠		
Ra Pe	13.3	13.3	3.3	13.3	44	13.3		0.00				Žì.											.]		
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	· •	-		-		-		12-0-				200		3			ì						1		
5. bs/h (for				-				100			-		٠								Ì				-
																		(1.E.)							
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)					h				-																
te: peak only)												. 9													
 Fuel Rate stroke @ pe or diesel on 	32.4	32.4	32.4	32.4	35	32.4						_								1 12					. :
Fue oke die	က	4	က	က	10	ല	-5					- 3 2 ()						7							
4. (for														2				- 2							
E						-				(1)															
			-				11114										İ								
PM (ss	Š	8	18	8	8	8				1				Ì											
.@ Gro	32	82	0.2	25	25	25				0	}		-												
3.BHP@RPM (SAE Gross)	29.9@2500	29.9@2500	29,9@2500	30@2500	32@2500	30@2500				2		75-1										-			
E 63	130	33	R	e.	ြင္မ	(0)																			
																									l i
<u> </u>										, I da		2.734		1								7-7-30 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-1-20 7-			
90	i	<u> </u>		<u> </u>	.	<u> </u>							-												
<u></u>	A D	2	Q-V		<u> </u>	A-D			71 2.1	2.0															
Ìġi	<u>ි</u>	K3M-DT	K3M-DT	K3M-DT	K3M-DT	K3M-DT				-	1	g		28		*									
2.Enaine Model			100	-	1	·							4.									-			
CV.							12.							.,				-						l ly	
j					-	-						1	1												
Ö	Y	H		=======================================	2H	<u> </u>							1												
) e) 	196	(20	Ž	DT1	DT2				1.5		1	4 ·	17						=			-		
jū	" 2	K3M-Y2DTB	K3M-Y2DTC	K3M-Y2DT11R	-Y2	K3M-Y2DT21RH				1.5															
1 Engine Code	K3M-Y2DTA	<u> </u>		<u> </u>	K3M-Y2DT12RH	\ <u>\$</u>											-								1
1		1_				ــــــــــــــــــــــــــــــــــــــ				Ш.	<u>.</u>	1	1_	F	J	1	<u>. </u>	J	ــــــــــــــــــــــــــــــــــــــ				!	. : : : .	<u></u>