

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED:** That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6CEXL015.AAC	15.0	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Engine Control Module			Loader, Tractor and Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
225 ≤ kW < 450	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		FEL	N/A	N/A	5.8	N/A	N/A	N/A	N/A	N/A
		CERT	--	--	5.7	0.5	0.11	8	2	22

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.**

Executed at El Monte, California on this 21<sup>ST</sup> day of November 2005.

  
 Allen Lyons, Chief  
 Mobile Source Operations Division

# Engine Model Summary Form

ATTACHMENT # 1 of 1

U-E-002-0522

**Manufacturer:** Cummins Inc.  
**Engine category:** Nonroad CI  
**EPA Engine Family:** 6CEXL015.AAC  
**Mfr. Family Name:** E103  
**Process Code:** New Submission

Don

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
8469:FR10455	QSX15-C	450@2100	225	159.0	1690@1400	356	168.1	DDI, TC, ECM, CAC
8469:FR10371	QSX15-C	450@2000	227	153.2	1670@1400	352	166.3	DDI, TC, ECM, C
8469:FR10346	QSX15-C	440@1800	244	147.8	1650@1400	348	164.5	DDI, TC, ECM, C
8469:FR10453	QSX15-C	425@2000	218	147.0	1595@1400	337	159.0	DDI, TC, ECM, C
8469:FR10454	QSX15-C	425@2000	218	147.0	1500@1400	313	148.0	DDI, TC, ECM, C
8469:FR10379	QSX15-C	400@2100	201	142.0	1453@1400	302	142.8	DDI, TC, ECM, C
8469:FR10316	QSX15-C	425@2100	210	148.5	1450@1400	297	140.3	DDI, TC, ECM, C
8469:FR10384	QSX15-C	425@1800	198	140.2	1452@1400	287	136.6	DDI, TC, ECM, C
8469:FR10488	QSX15-C	400@2100	201	142.0	1380@1400	280	132.4	DDI, TC, ECM, C
8469:FR10519	QSX15-C	435@2100	223	158.0	1468@1400	314	148.0	DDI, ECM, TC, C
8469:FR10590	QSX15-C	450@2100	225	159.0	1690@1400	356	168.21	DDI, TC, ECM, C
8469:FR10592	QSX15-C	400@2100	201	142.0	1453@1400	302	142.8	DDI, TC, ECM, C
8742:FR10316	QSX15-C	425@2100	210	148.5	1450@1400	297	140.3	DDI, ECM, TC, C
8742:FR10488	QSX15-C	400@2100	201	142.0	1380@1400	280	132.4	DDI, ECM, TC, C
8742:FR10379	QSX15-C	400@2100	201	142.0	1453@1400	302	142.8	DDI, ECM, TC, C