

DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY

EXECUTIVE ORDER U-R-004-0241 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2006	6JDXL03.0063	2.4, 3.0	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Dies	sel Injection, Smoke Puff	Limiter, Turbocharger	Loader, Tractor, Pump, Compressor, Generator Set, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr); and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION		EXHAUST (g/kW-hr) OPACITY (%)							(a)
 CLASS	STANDARD CATEGORY		нс	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		CERT	-	_	6.9	1.9	0.34	4	5	6

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 15th day of December 2005.

Mobile Source Operations Division

Engine Model Summary Form

Manufacturer:

John Deere Power Systems of Deere and

Engine category:

Nonroad Cl EPA Engine Family: 6JDXL03.0063

Family Name: 250TA

.ass Code:

New Submission

Attachment U-R.004.0241

5030TF270B 5030T ₹ 82.48 @2800 45.90 @2800 36.16 @2800 207.97 @1680 55.3 @1680 26.24 @1680 EM SPL DFI TC 4024TF270A 4024T 61.02 @2800 41.00 @2800 25.80 @2800 154.13 @1680 49.6 @1680 18.74 @1680 EM SPL DFI TC 5030TF270A 5030T 75.10 @2800 40.50 @2800 31.97 @2800 194.70 @1680 49.9 @1680 23.59 @1680 EM SPL DFI TC 4024TF270B 4024T 65.72 @2800 43.70 @2800 27.34 @2800 165.20 @1680 53.6 @1680 20.29 @1680 EM SPL DFI TC 5030TF003 5030T 75.10 @2800 40.50 @2800 31.97 @2800 194.70 @1680 49.9 @1680 23.59 @1680 EM SPL DFI TC 4024TT003 4024T 65.72 @2800 43.70 @2800 27.34 @2800 165.20 @1680 53.6 @1680 20.29 @1680 EM SPL DFI TC 4024TT001 4024T 65.72 @2800 41.00 @2800 25.80 @2800 154.13 @1680 49.6 @1680 18.74 @1680 EM SPL DFI TC 5030TT001 5030T 75.10 @2800 43.70 @2800	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
5030TF270A 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 4024TF270B 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TF270C 5030T 80.47@1800 63.20@1800 32.04@1800 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT003 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 4024TT003 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT002 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680<	5030TF270B	5030T	82.48@2800	45.90@2800	36.16@2800	207.97@1680	55.3@1680	26.24@1680	EM SPL DFITC
4024TF270B 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TF270C 5030T 80.47@1800 63.20@1800 32.04@1800 EM SPL DFI TC EM SPL DFI TC 5030TT003 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 4024TT003 4024T 65.72@2800 43.70@2800 27.34@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@16	4024TF270A	4024T	61.02@2800	41.00@2800	25.80@2800	154.13@1680	49.6@1680	18.74@1680	EM SPL DFI TC
5030TF270C 5030T 80.47@1800 63.20@1800 32.04@1800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT003 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 4024TT003 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T \$6.33@2400 37.60@2400 20.29@2400 146.76@1440<	5030TF270A	5030T	75.10@2800	40.50@2800	31.97@2800	194.70@1680	49.9@1680	23.59@1680	EM SPL DFI TC
5030TT003 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 4024TT003 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T \$4.52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV08 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@144	4024TF270B	4024T	65.72@2800	43.70@2800	27.34@2800	165.20@1680	53,6@1680	20.29@1680	EM SPL DFITC
4024TT003 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T 34.52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV08 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.31@2400 174.78@144	5030TF270C	5030T	80.47@1800	63.20@1800	32.04@1800				EM SPL DFI TC
4024TT001 4024T 61.02@2800 41.00@2800 25.80@2800 154.13@1680 49.6@1680 18.74@1680 EM SPL DFI TC 4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T 34.52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 174.78@1440 43@1440 17.42@1440 EM SPL DFI TC	5030TT003	5030T	75.10@2800	40.50@2800	31.97@2800	194.70@1680	49.9@1680	23.59@1680	EM SPL DFI TC
4024TT002 4024T 65.72@2800 43.70@2800 27.34@2800 165.20@1680 53.6@1680 20.29@1680 EM SPL DFI TC 5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T 54 52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFI TC 4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFI TC	4024TT003	4024T	65.72@2800	43.70@2800	27.34@2800	165.20@1680	53.6@1680	20.29@1680	EM SPL DFITC
5030TT001 5030T 75.10@2800 40.50@2800 31.97@2800 194.70@1680 49.9@1680 23.59@1680 EM SPL DFI TC 5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T 33 52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFI TC 4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFI TC	4024TT001	4024T	61.02@2800	41.00@2800	25.80@2800	154.13@1680	49.6@1680	18.74@1680	EM SPL DFI TC
5030TT002 5030T 82.48@2800 45.10@2800 35.50@2800 209.44@1680 55.3@1680 26.24@1680 EM SPL DFI TC 4024TLV06 4024T χ ^α ₁ 52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFI TC 4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFI TC 4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFI TC	4024TT002	4024T	65.72@2800	43.70@2800	27.34@2800	165.20@1680	53.6@1680	20.29@1680	EM SPL DFI TC
4024TLV06 4024T 34 52.30@2400 37.60@2400 20.29@2400 146.76@1440 47.2@1440 15.28@1440 EM SPL DFITC 4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFITC 4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFITC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFITC	5030TT001	5030T	75.10@2800	40.50@2800	31.97@2800	194.70@1680	49.9@1680	23.59@1680	EM SPL DFITC
4024TLV07 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 EM SPL DFITC 4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFITC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFITC	5030TT002	5030T	82.48@2800	45.10@2800	35.50@2800	209.44@1680	55.3@1680	26.24@1680	EM SPL DFITC
4024TLV08 4024T 61.69@2400 43.20@2400 23.31@2400 174.78@1440 55.3@1440 17.91@1440 EM SPL DFI TC 5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFI TC	4024TLV06	4024T 3	ዓ 52.30@2400	37.60@2400	20.29@2400	146.76@1440	47.2@1440	15.28@1440	EM SPL DFITC
5030TLV03 5030T 57.67@2400 34.60@2400 23.33@2400 170.36@1440 43@1440 17.42@1440 EM SPL DFI TC	4024TLV07	4024T	56.33@2400	39.80@2400	21.50@2400	160.77@1440	50.9@1440	16.50@1440	EM SPL DFITC
	4024TLV08	4024T	61.69@2400	43.20@2400	23.31@2400	174.78@1440	55.3@1440	17.91@1440	EM SPL DFI TC
5030TLV04 5030T 68.40@2400 40.10@2400 27.03@2400 196.91@1440 49.9@1440 20.20@1440 EM SPL DFI TC	5030TLV03	5030T	57.67@2400	34.60@2400	23.33@2400	170.36@1440	43@1440	17.42@1440	EM SPL DFITC
	5030TLV04	5030 T	68.40@2400	40.10@2400	27.03@2400	196.91@1440	49.9@1440	20.20@1440	EM SPL DFI TC

Engine Model Summary Form

Manufacturer:

John Deere Power Systems of Deere and

Engine category:

Nonroad CI

EPA Engine Family: 6JDXL03.0063

Mfr Family Name:

250TA

Code:

Running Change

4-17-004-0241

4.Fuel Rate: mm/stroke @ peak HP (for diesel only) 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) 7.Fuel Rate: mm/stroke@peak 3.BHP@RPM (SAE Gross) 6.Torque @ RPM (SEA Gross) 8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930 1.Engine Code 2.Engine Model torque 4024TF270F 4024T 56.33@2400 39.80@2400 21.50@2400 160.77@1440 50.9@1440 16.50@1440 ... EM SPL DFITC ...