

## DEERE POWER SYSTEMS GROUP OF DEERE & COMPANY

EXECUTIVE ORDER U-R-004-0262 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2006			Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Dies	sel Injection, Turbocharge	er, Smoke Puff Limiter	Tractor, Pump, Compressor, Generator Set, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
POWER CLASS			HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	ŞTD	N/A	N/A	7.5	5.0	0.40	20	15	50
		FEL	-	-	6.5	-	0.31	-	•	,
		CERT	-	•	5.8	1.4	0.24	8	6	18

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2005.

Allen Lyons, Chief

Mobile Source Operations Division

Rephael Surrout

## **Engine Model Summary Form**

Manufacturer:

John Deere Power Systems of Deere and

Engine category: Nonroad CI

EP4 Engine Family: 6JDXL04.5083

amily Name: 350TM

Process Code:

**New Submission** 

Attachment U-R-004-0762

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
4045TF270B	4045T	99.24@2500	69.60@2500	39.16@2500	272.13@1400	85.8@1400	27.06@1400	EM SPLTC DFI
4045TF270C	4045T	99.24@2200	76.80@2200	38.01@2200	284.67@1400	89.7@1400	28.25@1400	EM SPL TC DFI
4045TF270D	4045T	84.49@2500	59.20@2500	33,27@2500	245.58@1000	75,6@1000	17.02@1000	EM SPL TC DFI
4045TLV53	4045T	81.14@2400	61.40@2400	33.07@2400	228.62@1400	72.6@1400	22.93@1400	EM SPL TC DFI
4045TLV54	4045T	91.19@2400	67.80@2400	36.60@2400	258.12@1400	81.2@1400	25,58@1400	EM SPL TC DFI
4045TZ270	4045T	99.24@2200	76.80@2200	38.01@2200	284.67@1400	89.7@1400	28.25@1400	EM SPL TC DFI
						The state of the state of		