CNH ENGINE CORPORATION, INC.

EXECUTIVE ORDER U-R-011-0106 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2006	6X9XL0540AAC	8.8	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Powertrain Control Module			Tractor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
225 ≤ kW < 450	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		FEL	N/A	N/A	5.8	N/A	N/A	N/A	N/A	N/A
		CERT			5.0	1.6	0.17	3	1	9

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order

Executed at El Monte, California on this

__ day of November 2005.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Summary Form

9010-110-8-11

Manufacturer: CNH Engine Corp.

Engine category: Nonroad CI

EPA Engine Family: 6X9XL0540AAC

Mfr Family Name: C563

Process Code: New Submission CORRECTION

	4				
8					
8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930	109.0 DZ PCM,TC,CAO	O	3-14		
ξò	₹.	/ PCM,TC,CAC			
ა ₩	O.	<u>ပ</u>	215		
e s	\mathbf{O}	ပ္	22.13		
SSi Del		₩.			
Ε̈́g	4	옭			
H. i≷	ĭ	ĭ	vă.		
ိ ရိ		XIII	und f		
_	Z	->			
ž			307 P		
;; ŏ					
8.Fuel Rate: hr)@peak tor	0	102.0.	100		
ea T	0	\mathbf{z}			
e e	2	2			
۳. چ.					
e √s					
<u>ق</u>		212			
			VEL - 13		
¥	11				
7.Fuel Rate: mm/stroke@peak torque					
7.Fuel Rate: n/stroke@pe torque	4	ശ			
uel Ra troke@ torque	က	216	40		
e E e		3.77			
π. 1 8	14.2				
'` E					
_			4,3		
			£3.3.		
-			2		
6.Torque @ RPM (SEA Gross)	1181@1400	133@1400			
S 28	₹.	<u> 7</u>			
Torque @ RPI (SEA Gross)	(a)	(0)			
A G	=	8			
БЖ	Ω.	က္			
17.00		Sept.			
9	1				
	123				
۵.		7.			
≒ ≩		2.52	333		
을 뚫 등	in	$\dot{\circ}$			
<u>ୟୁ ସୁ ଖ</u>	N	တ			
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	Š	గా	1		
또 주	5.5				
5. for					
₽ 5					
_		Ē.	17.5		
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	35.				
X S		Language Engli	13.74		
on See					
4.Fuel Rate: stroke @ pea or diesel only	22	22			
e (e	· CO	Ě	24.		
引きさ					
4 st 7			2.1		
Ē			1.0		
E	122				
	4.9				
5 ~	O	O	1.50		
SS	Ō	ō			
3.BHP@RPM (SAE Gross)	333@2000	365@2100			
9	0	0	42		
# ₹	8	35			
₩, 65	m	ĕ	4.7		
	A.				
			ļ,		
75		4334	100		
ďe					
9	6TAA-9004	6TAA-9004	10.		
2	8	90			
ne	4	4	100		
<u>.</u>	3	3			
ភ	15	Ę			
2.1		<u>ب</u>			
	W 6				
43			71.		
å	8	8			
8	Ą	ŏ			
0	တ	6			
1.Engine Code 2.Engine Model	K	3478;FR91900	17		
<u>ق</u>	1	- E			
ய்	5	12			
- -	8600:FR91481	8	55.		