



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2006	6KBXL02.4ECD	1.826, 2.434	Diesel	5000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Electronic Control Module			Loader, Other Industrial Equipment	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NO_x), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NO_x), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
			HC	NO _x	NMHC+NO _x	CO	PM	ACCEL	LUG	PEAK
19 ≤ kW < 37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT	--	--	6.5	2.2	0.40	3	4	4

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 29th day of December 2005.


for Allen Lyons, Chief
Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: KUBOTA Corporation
Engine category: Nonroad CI
EPA Engine Family: 6KBXL02.4ECD
Mfr Family Name: N/A
Process Code: New Submission

Attachment
U-R-025-0249

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
4IRX3N2	4IRX3N2	48.9@2600	32.8	19.1	117.7@1700	36.3	13.8	N/A ODI ECU
D1803-M-DI-ES01	D1803-M-DI-ES	39.2@2600	35.5	15.5	93.3@1600	39.6	10.6	N/A
D1803-M-DI-ES02	D1803-M-DI-ES	38.1@2600	34.2	14.9	91.8@1700	37.5	10.7	N/A
V2403-M-DI-ES01	V2403-M-DI-ES	48.8@2600	32.6	18.9	122.3@1700	38.4	14.6	N/A
V2403-M-DI-ES02	V2403-M-DI-ES	48.9@2600	32.8	19.1	117.7@1700	36.3	13.8	N/A
V2403-M-DI-ES03	V2403-M-DI-ES	46.8@2400	33.9	18.2	114.6@1500	35.8	12.0	N/A
V2403-M-DI-ES04e	V2403-M-DI-ES	37.1@1950	32.5	14.2	108.3@1200	34.0	9.1	Electronic EC
V2403-M-DI-ES05	V2403-M-DI-ES	48.9@2700	33.3	20.1	117.0@1600	37.1	13.3	N/A

Engine Model Summary Form

CONFIDENTIAL

Manufacturer: **KUBOTA Corporation**
 Engine category: **Nonroad CI**
 EPA Engine Family: **6KBXL02.4ECD**
 Mfr Family Name: **N/A**
 Process Code:

Attachment
 EO#U-R-025-6249

1. Engine Code	2. Engine Model	3. BHP@RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke@peak torque	8. Fuel Rate: (lbs/hr)@peak torque	9. Emission Control Device Per SAE J1930
4IRX3N2	4IRX3N2	48.9@2600	32.8	19.1	117.7@1700	36.3	13.8	EM DI
D1803-M-DI-ES01	D1803-M-DI-ES	39.2@2600	35.5	15.5	93.3@1600	39.6	10.6	EM
D1803-M-DI-ES02	D1803-M-DI-ES	38.1@2600	34.2	14.9	91.8@1700	37.5	10.7	EM
V2403-M-DI-ES01	V2403-M-DI-ES	48.8@2600	32.6	18.9	122.3@1700	38.4	14.6	EM
V2403-M-DI-ES02	V2403-M-DI-ES	48.9@2600	32.8	19.1	117.7@1700	36.3	13.8	EM
V2403-M-DI-ES03	V2403-M-DI-ES	46.8@2400	33.9	18.2	114.6@1500	35.8	12.0	EM
V2403-M-DI-ES04e	V2403-M-DI-ES	37.1@1950	32.5	14.2	108.3@1200	34.0	9.1	Electronic EC
V2403-M-DI-ES05	V2403-M-DI-ES	48.9@2700	33.3	20.1	117.0@1600	37.1	13.3	EM
V2403-M-DI-ES06	V2403-M-DI-ES	45.7@2400	33.1	17.8	115.0@1500	35.9	12.0	EM