Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

**IT IS ORDERED AND RESOLVED**: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)			
2006	6H3XL1.13MSL	1.131	Diesel	5000			
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION				
	Indirect Diesel Inje	ection	Loader				

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)				OPACITY (%)			
			нс	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
19 <u>&lt;</u> KW<37	Tier 2	STD	N/A	N/A	7.5	5.5	0.60	20	15	50
		CERT			4.5	1.5	0.36	7	6	12

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

## This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_2 $2l^{\frac{2l}{2}}$ \_\_\_\_ day of December 2005.

Raphael Sumaint

Allen Lyons, Chief Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT 10F

anufacturer: Ishikawajima-Shibaura Machinery Co., Ltd. ngine category: Nonroad Cl PA Engine ramiy: 6H3XL1.13MSL

New Submission

A/A

Afr Family Name:

rocess Code:

UN-026-0167

8.Fuel Rate: 9.Emission Control (bs/hr)@peak torque Device Per SAE J1930 Ē E ī Ē Ē Ŀ I Ē Ē. 9.3+/-0.5 8.5+/-0.5 8.5+/-0.5 9.0-/+9.6 9.5+/-0.7 8.3+/-0.5 8.7+/-0.5 9.7+/-0.7 9,5+/-0.7 7.Fuel Rate: mm/stroke@peak 23.5+/-1.4 23.5+/-1.3 24,1+/-1.8 24.1+/-1.8 24.4+/-1.5 23.5+/-1.4 24,0+/-1.5 22.9+/-1.4 25.5+/-1.7 torque 6.Torque @ RPM (SEA Gross) 50.2@2200 50.2@2200 51.6@2400 69,6@1800 69.6@1800 51.9@2300 49.3@2100 48.8@2300 50.2@2400 5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only) 12.7+/-0.3 10.9+/-0.6 10.9+/-0.6 12.6+/-0.8 13.5+/-0.8 14.9+/-1.0 11.6+/-0.9 13.4+/-0.9 12.2+/-0.7 mm/stroke @ peak HP (for diesel only) 22.0+/-0.6 22.7+/-1.4 23.1+/-1.2 23.1+/-1.2 22.0+/-1.3 22.6+/-1.5 24.6+/-1.5 19.5+/-1.4 22.6+/-1.5 4.Fuel Rate: 29.1@3500 3.BHP@RPM (SAE Gross) 26.0@2850 26.0@2850 28.2@3400 33.0@2800 35.5@3000 29.9@3600 26.4@3000 25.6@3600 2.Engine Model HN33/2800 HH28/3400 HH30/3600 HN36/3000 HH26/3000 HH26/3600 26/2850 26/2850A 29/3500 1.Engine Code S773L-C 404C-15 404C-15 S773L-C S773L-C 403C-11 403C-11 403C-11 403C-11