EXECUTIVE ORDER U-R-028-0270 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2006	6YDXM0.57P2N	0.570	Diesel	3000		
	FEATURES & EMISSION		TYPICAL EQUIPMENT	APPLICATION		
	Indirect Diesel Inje	ection	Marine Engine			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbons (HC), oxides of nitrogen (NOx), or non-methane hydrocarbons plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION		EXHAUST (g/kW-hr)				OPACITY (%)				
	POWER CLASS	STANDARD CATEGORY		HC	NOx	NMHC+NOx	СО	PM	ACCEL	LUG	PEAK
	8 ≤ kW < 19	Tier 2	STD	N/A	N/A	7.5	6.6	0.80	N/A	N/A	N/A
			CERT			4.5	0.9	0.22			

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_

\_\_\_ day of December 2005.

Allen Lygos, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

EO#U-R-U28-0270 ATTACHMENT, PIOF!

Manufacturer: Yanmar Co., Ltd.

Engine category: Nonroad CI

EPA Engine Family: 6YDXM0.57P2N

Mfr Family Name: N/A

Process Code: New Submission

		TMINE 2			.: <u> </u>			47.4	Se . 1
9.Emission Control Device Per SAE J1930				59-57 V	1	2.0			
\$ E		****		[華]			3.4	May 1	
្កក្នុ									
S S	5							L T	- 4.
e ŝi	101, EM								
E 9		- 200						K49.	
<u>ਜ਼</u> :ଚ	Δ _						5.4		- 6
٠, <del>۵</del>			No. 1		144.04		1004		
•		188.00				longs:	27:34		
큣				. 1			127		ļ.
ق نۆ									1
쫎첉	4						1 3 3		b
필층	N/A							1	
8.Fuel Rate: (lbs/hr)@peak torque		A			3.4				
ຶ່ຮ	\$3.5d	6.33		1:01					
€				1 1			1 7	1.78	1.
		202							
×		201					9.77 <del>4</del> 5.5 9.772.70	15.89	
ğ ğ		14.5		9.93					
7.Fuel Rate: mm/stroke@peak torque	××	5-250	(m. 7/1)			1.33			Ŀ
a S S	4.9							14.3	á
7.7 18/		200							2
Ē					[279]	Y. (2.2.4)	25.		
				Ŷ		Kad	13.4		
		12.000							
6.Torque @ RPM (SEA Gross)	*****	E.		1 2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1.794		V 18	38	10
유 (S		275			1.33	1.0021	1884	249e-	
@ දි	NA	100	24.2574	(4.5 J				100	ŀ.
Σď	Z	-27\025 -27\225			1887		8.3		1
E N	2.7600 T	****	8000 344		1.30			POR A	
μ. Έ	2000	25100					2.4	13.39	
•	- T	W 2002							ľ
	2 - 12 1 2 - 12 1	A 22 (7)	X42-4		2.007 50 - 0	.35			l K
ᇁᇰ			125. V				222		12
∃ ¥ €				77.7	13.33				
සු <u>ප</u> දි	O	3.4		200			2.0.1	777	K
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.9	概念		60	1273	W	200	4.47	
正言章	<b>***</b>	1000	(A)	F1 50 5			377	4.44	i
£ bs €	32.55					164	2 53	Est	
€ ~		122				4.5	500	17,20	b
α.				19-4	1950	1002			
Ĩ.			2.54	-		500.00			i i
eat L		17 X 20 X			10000	A-1-74	P2.3		
E Q S	<b>J</b>					124 S		143	ľ
- 0 38 - 0 38	17.4								1
근용ㅎ				0.1	1985	(30)			
/st 4	1			237	M0.3			15.55	
4.Fue! Rate: mm/stroke @ peak HP (for diesel only)	7.8		18.873	200,1,50 A	1985-1		72.3	M-5/	1
_			20						
		233		- 7	1				1.
3.BHP@RPM (SAE Gross)	0								
35 S	13.8/3600	5.5.4			1 1				
@ ල	3							1	
붗빝	8				1		- 1	1. 1	
3.E (S)	2	12.7							
	131						1		1
		-				1 1			
-				and the same				491	
å									
2.Engine Model	2YM15	1							
(1)	Ξ								
.≝	⋛					ŀ			
ρ	~								
竝						The state of the s			
2									1
1.Engine Code		.							
ŏ									ļ
Ö									1
ne.	NA								
ğ	2								
иï				-				:	
<del>~-</del>							1		