

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)
2007	7CEXL015.AAE	15.0	Diesel	8000
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION	
Direct Diesel Injection, Turbocharger, Charge Air Cooler, Engine Control Module			Loader, Tractor and Compressor	

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):


RATED POWER CLASS	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
			HC	NOx	NMHC+NOx	CO	PM	ACCEL	LUG	PEAK
225 ≤ kW < 450	Tier 3	STD	N/A	N/A	4.0	3.5	0.20	20	15	50
		CERT	--	--	3.6	0.7	0.09	16	2	23

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this 6 day of November 2006.



Annette Hebert, Chief
 Mobile Source Operations Division

Engine Model Summary Form

ATTACHMENT B 1 of 1

U-12-002-036S

Manufacturer: **Cummins Inc.**
 Engine category: **Nonroad CI**
 EPA Engine Family: **7CEXL015.AAE**
 Mfr Family Name: **G103**
 Process Code: **New Submission**

1. Engine Code	2. Engine Model	3. BHP @ RPM (SAE Gross)	4. Fuel Rate: mm/stroke @ peak HP (for diesel only)	5. Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6. Torque @ RPM (SEA Gross)	7. Fuel Rate: mm/stroke @ peak torque	8. Fuel Rate: (lbs/hr) @ peak torque	9. Emission Control Device Per SAE J1930
8760:FR10601	QSX15-C	600@1800	350	212.5	1875@1350	411	187.0	DDI,ECM,TC,CAC
8760:FR10568	QSX15-C	600@2100	317	224.5	1875@1400	408	192.5	DDI,ECM,TC,C
8760:FR10569	QSX15-C	560@1800	341	207.0	1875@1350	411	187.0	DDI,ECM,TC,C
8760:FR10593	QSX15-C	535@2100	283	200.5	1873@1400	408	192.5	DDI,ECM,TC,C
8760:FR10595	QSX15-C	630@2100	322	228.1	1875@1400	375	176.9	DDI,ECM,TC,C
8761:FR10571	QSX15-C	510@1800	307	186.5	1743@1350	397	172.5	DDI,ECM,TC,C
8761:FR10574	QSX15-C	450@1800	274	166.5	1550@1350	346	157.5	DDI,ECM,TC,C
8761:FR10570	QSX15-C	520@2100	280	198	1743@1400	379	179.0	DDI,ECM,TC,C
8761:FR10565	QSX15-C	485@2000	261	176	1783@1400	388	183.0	DDI,ECM,TC,C
8761:FR10583	QSX15-C	500@2000	280	189	1743@1400	379	179.0	DDI,ECM,TC,C
8761:FR10579	QSX15-C	560@1800	344	208.5	1743@1350	379	172.5	DDI,ECM,TC,C
8761:FR10573	QSX15-C	450@2000	253	170.5	1550@1400	344	162.5	DDI,ECM,TC,C
8761:FR10572	QSX15-C	450@2100	241	171	1550@1400	344	162.5	DDI,ECM,TC,C
8761:FR10642	QSX15-C	500@1800	301	183	1743@1350	379	172.5	DDI,ECM,TC,C
8761:FR10577	QSX15-C	500@2100	268	190	1743@1400	379	179	DDI,ECM,TC,C
8761:FR10581	QSX15-C	400@2100	217	154	1452@1400	322	152.2	DDI,ECM,TC,C
8761:FR10596	QSX15-C	375@1800	235	142.5	1346@1350	301	136.9	DDI,ECM,TC,C
8762:FR10582	QSX15-C	390@2000	217	146.6	1346@1400	295	137.9	DDI,ECM,TC,C
8760:FR10601	QSX15-C	600@1800	350	212.5	1875@1400	408	192.5	DDI,ECM,TC,C
8760:FR10569	QSX15-C	560@1800	341	207.0	1875@1400	408	192.5	DDI,ECM,TC,C
8761:FR10571	QSX15-C	510@1800	307	186.5	1743@1400	375	177.0	DDI,ECM,TC,C
8761:FR10579	QSX15-C	560@1800	344	208.5	1743@1400	375	177.0	DDI,ECM,TC,C
8761:FR10623	QSX15-C	500@1800	301	183.0	1743@1400	375	177.0	DDI,ECM,TC,C
8761:FR10596	QSX15-C	375@1800	235	142.5	1346@1400	301	142.0	DDI,ECM,TC,C
8761:FR10574	QSX15-C	450@1800	274	166.5	1550@1400	341	160.8	DDI,ECM,TC,C
8761:FR10659	QSX15-C	435@2100	232	164.0	1469@1400	320	151.0	DDI,ECM,TC,C
8761:FR10660	QSX15-C	485@2100	257	181.8	1637@1400	359	169.4	DDI,ECM,TC,C