

## JOHN DEERE POWER SYSTEMS OF DEERE

EXECUTIVE ORDER U-R-004-0299

New Off-Road

Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2007	7JDXL04.5042	4.5	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger, Smoke Puff Limiter, Electronic Control Module			Loader, Tractor, Pump, Compressor, Generator Set, Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kW-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kW-hr)					OPACITY (%)		
POWER CLASS			нс	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
37 ≤ kW < 75	Tier 2	STD	N/A	N/A	7.5	5.0	0.40	20	15	50
		FEL	-	-	-	-	0.36	-	-	-
		CERT	-	-	5.7	1.1	0.32	7	3	18

**BE IT FURTHER RESOLVED:** That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

**BE IT FURTHER RESOLVED:** That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of December 2006.

Annette Hebert, Chief

Mobile Source Operations Division

## **Engine Model Summary Form**

Manufacturer: John Deere Power Systems of Deere and

Engine category: Nonroad Cl

⇒A Engine Family: 7JDXL04.5042

Mfr Family Name: 350TD

Pro ins Code: New Submission

Attach ment E0# U-R-004-0299

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for dieset only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels onty)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J193	
4045TF275A	4045T	99.24@2500	75,00@2500	34.00@2500	296.98@1500	99.8@1500	41.89@1500	EM EC SPL	DOI,
4045TRT70	4045T	80.47@2350	54.20@2350	32.63@2350	250.59@1400	85@1400	25.80@1400	EM EC SPL	1
4045TRT71	4045T	90.52@2350	69.60@2350	35.28@2350	277.00@1400	93.5@1400	28.22@1400	EM EC SPL	ा
4045TRT72A	4045T	99.24@2200	79.00@2200	37.70@2200	288.06@1500	95@1500	31.09@1500	EM EC SPL	
4045TRT73	4045T	90.52@2200	71.00@2200	35.28@2200	276.55@1400	89@1400	28.00@1400	EM EC SPL	
4045TRT74	4045T	99.24@2350	71.50@2350	37.79@2350	290.57@1500	91.5@1500	30.89@1500	EM EC SPL	
4045TL270	4045T	77.78@2300	59.50@2300	29.55@2300	238.94@1500	77.6@1500	25.14@1500	EM EC SPL	
4045TL272	4045T	92.54@2300	71.30@2300	35.50@2300	281.72@1500	91.9@1500	29.77@1500	EM EC SPL	
4045TL271	4045T	84.49@2300	64.90@2300	32.41@2300	257.38@1500	83.8@1500	27.34@1500	EM EC SPL	<u> </u>
4045TF278	4045T	99.24@2200	79.00@2200	37.70@2200	288.06@1500	95@1500	31.09@1500	EM EC SPL	-
		MgC Colored Street							
<u>A., B., A.</u>						<u> </u>			
			the second of the second						
		**************************************							
									-